



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L
FARBE	Blast/Gray/Neon Green
RAHMEN	ALUXX SLR-Grade Aluminum
GABEL	Composite, ALUXX OverDrive Steerer
KOMPONENTEN	
LENKER	Giant Contact Low , 31.8mm
VORBAU	Giant Contact, 31.8, 8 Degree
SATTELSTÜTZE	Giant D-Fuse, Composite
SATTEL	Contact (Neutral)
ANTRIEB	
SCHALTHEBEL	SRAM GX Trigger
UMWERFER	SRAM X5
SCHALTWERK	SRAM GX
BREMSEN	TRP Slate X2
KASSETTE	SRAM PG1020, 11-36
KETTE	KMC X10 with Missing Link
KURBEL	SRAM S1000, 28/42
LAUFRÄDER	
TRETLAGER	SRAM GXP
FELGEN	Giant S-X2 Wheelset, Tubeless
REIFEN	Giant CrossCut Gravel 2, 700x50Tubeless
EXTRAS	X-DFender/ ChainStay Protector, Tubeless Upgradeable

MODELL-MERKMALE

- ALUXX SLR-grade aluminum frame with D-Fuse composite seatpost
- Giant composite fork with alloy/composite OverDrive hybrid steerer
- SRAM GX 1x10-speed drivetrain
- TRP Slate X2 hydraulic disc brakes
- Giant S-X2 Disc wheelset with Giant CrossCut Gravel 2 tubeless tires
- Color: Blast/Gray/Neon Green



GEOMETRIEDATEN

RAHMEN	XS	S	M	L	XL
Sitzrohrlänge (mm)	390	420	460	510	550
Sitzrohrwinkel	73.0°	73.0°	73.0°	72.0°	71.5°
Oberrohrlänge (mm)	580	585	595	605	620
Steuerrohr-Länge (mm)	100	125	150	170	190
Steuerrohr-Winkel	71.5°	71.5°	71.5°	72.0°	72.0°
Gabelneigung (mm)	42	42	42	42	42
Trail (mm)	78	78	78	75	75
Radstand (mm)	1061	1067	1078	1071	1080
Kettenstreben-Länge (mm)	450	450	450	450	450
Tretlager-Höhe (mm)	70	70	70	70	70
Stack (mm)	555	578	602	623	642
Reach (mm)	403	405	408	410	411
Überstandshöhe (mm)	696	724	754	795	864
Lenkerbreite (mm)	640	640	640	690	690
Vorbaulänge (mm)	70	70	80	90	100
Kurbellänge (mm)	170	170	175	175	175
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbaenderungen vorbehalten.