

XTC ADVANCED 29ER 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Matt Neon Red/Gloss Carbon/Black
RAHMEN	Giant Advanced-Grade Composite with Horizontal Dropouts
GABEL	RockShox SID RL Remote, 100mm Travel, Charger Damper, OneLoc, Boost 15x110, Maxle Stealth, Tapered
KOMPONENTEN	
LENKER	Giant Contact SL XC Flat, 750 x 31.8mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Composite, 27.2x400mm
SATTEL	Giant Contact SL (Forward)
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
SCHALTWERK	SRAM GX Eagle
BREMSEN	SRAM Level TL [F] 180mm [R] 160mm, Hydraulic Disc
BREMSHEBEL	SRAM Level TL
KASSETTE	SRAM GX Eagle, 10-50t
KETTE	SRAM GX
KURBEL	TruVativ Stylo 6k Eagle, 34t
LAUFRÄDER	
TRETLAGER	SRAM GXP PressFit
FELGEN	Giant XCR 1 29" Composite WheelSystem [F] Boost 15x110 [R] Boost 12x148 XD Driver Body
REIFEN	Maxxis IKON 29x2.2 Folding, 120 TPI, 3C/TR/EXO, Tubeless
EXTRAS	Factory Tubeless

MODELL-MERKMALE

- Advanced-grade composite frame with horizontal dropouts
- RockShox SID RL Remote 100mm-travel fork with OneLoc remote lockout
- SRAM GX Eagle 1x12-speed drivetrain
- SRAM Level TL hydraulic disc brakes
- Giant XCR 1 Composite WheelSystem with Maxxis Ikon tubeless tires
- Color: Matt Neon Red/Gloss Carbon/Black



GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	390	440	490	535
Sitzrohrwinkel	73.0°	72.5°	72.0°	72.0°
Oberrohrlänge (mm)	585	605	625	645
Steuerrohr-Länge (mm)	95	95	105	115
Steuerrohr-Winkel	70.0°	70.0°	70.0°	70.0°
Gabelneigung (mm)	51	51	51	51
Trail (mm)	82	82	82	82
Radstand (mm)	1074	1088	1102	1122
Kettenstreben-Länge (mm)	425	425	425	425
Tretlager-Höhe (mm)	60	60	60	60
Stack (mm)	612	612	621	631
Reach (mm)	398	412	423	440
Überstandshöhe (mm)	739	765	797	827
Lenkerbreite (mm)	750	750	750	750
Vorbaulänge (mm)	60	70	80	90
Kurbellänge (mm)	170	175	175	175
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.