



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L
FARBE	Gun Metal Black / Neon Orange / Charcoal
RAHMEN	Advanced-Grade Composite, ALUXX SL Rear Triangle
GABEL	Fox 34 Float Performance Elite, 130mm travel, FIT4 Damper, Boost 15x110mm KaBolt, tapered steerer
DÄMPFER	Fox Float DPS Performance Elite, trunnion mount
KOMPONENTEN	
LENKER	Giant Contact SL Trail, 780 x 31.8mm
VORBAU	Giant Contact SL
SATTELSTÜTZE	Giant Contact Switch S dropper post with remote lever, 30.9mm
SATTEL	Contact SL (neutral)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM NX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM NX Eagle
BREMSEN	SRAM Guide RS [F] 180mm [R] 160mm, hydraulic disc
BREMSHEBEL	SRAM Guide RS
KASSETTE	SRAM NX Eagle, 11x50
KETTE	SRAM NX Eagle
KURBEL	TruVativ Descendent 6k Eagle Dub, Boost, 30
LAUFRÄDER	
TRETLAGER	SRAM GXP Dub Press Fit
FELGEN	Giant TRX 1 Composite DBL WheelSystem, hookless, 30mm inner width, tubeless
NABE	Giant TRX 1 DBL WheelSystem, pawl driver, Boost, thru-axle, 28h
SPEICHEN	Giant TRX 1 DBL WheelSystem; Dynamic Balanced Lacing, Butted Stainless Steel
REIFEN	Maxxis high Roller II 27.5x2.3, 60 tpi, EXO, TR, tubeless

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, ALUXX SL Rear Triangle
- Gabel: Fox 34 Float Performance Elite, 130mm travel, FIT4 Damper, Boost 15x110mm KaBolt, tapered steerer
- Schalthebel: SRAM NX Eagle, 1x12
- Kurbel: TruVativ Descendent 6k Eagle Dub, Boost, 30
- Farbe: Gun Metal Black / Neon Orange / Charcoal

GEOMETRIEDATEN

RAHMEN	XS	S	M	L	XL
Sitzrohrlänge (mm)	370	390	440	490	535
Sitzrohrwinkel	72.9°	72.9°	72.9°	72.9°	72.9°
Oberrohrlänge (mm)	565	585	605	625	645
Steuerrohr-Länge (mm)	95	95	100	110	120
Steuerrohr-Winkel	67.4°	67.4°	67.4°	67.4°	67.4°
Gabelneigung (mm)	42	42	42	42	42
Trail (mm)	102	102	102	102	102
Radstand (mm)	1094	1114	1134	1155	1176
Kettenstreben-Länge (mm)	428	428	428	428	428
Tretlager-Höhe (mm)	21	21	21	21	21
Stack (mm)	573	574	579	588	597
Reach (mm)	391	411	429	446	463
Überstandshöhe (mm)	695	714	737	774	806
Lenkerbreite (mm)	780	780	780	780	780
Vorbaulänge (mm)	40	50	50	60	70
Kurbellänge (mm)	170	170	175	175	175
Radgrösse	27.5"	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.