

FATHOM E+ 2 PRO 29ER



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Cobalt BlueMatte Black
RAHMEN	ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
GABEL	Rock Shox Recon RL 120mm travel, Tapered 1½ - 1⅝" steerer, 110x15QR, lockout
KOMPONENTEN	
LENKER	Giant Connect TR, 31,8x780mm
VORBAU	Giant Connect
SATTELSTÜTZE	Giant 30,9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Contact, Neutral
ANTRIEB	
SCHALTHEBEL	Shimano Deore
SCHALTWERK	Shimano Deore XT, 10-Speed, Shadow+
BREMSEN	Shimano BR-MT500, hydraulic disc, 180/200mm
BREMSHEBEL	Shimano BL-MT500, i-spec II
KASSETTE	Shimano HG50-10, 11-36T, 10-Speed
KETTE	KMC e.10 Turbo, e-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
SPEICHEN	Sapim E-Lite [r] Race [f], e-bike optimized
REIFEN	Maxxis Forekaster 29x2.35, foldable, 60 TPI, EXO, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger (60% charge in 60minutes)
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro, 360% supported by YAMAHA
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl ONE, remote button
BATTERY	Giant EnergyPak 500, 36V 13.8Ah integrated Lithium-Ion

MODELL-MERKMALE

- Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
- Giant EnergyPak500 lithium-ion battery for longest range
- RockShox Recon RL 120mm suspension fork
- Shimano Deore/XT 1x10 speed drivetrain
- Shimano hydraulic disc brakes
- Color: Cobalt Blue, Matte Black

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	405	465	505	535
Sitzrohrwinkel	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	575	600	625	650
Steuerrohr-Länge (mm)	105	115	125	140
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	51	51	51	51
Trail (mm)	96	96	96	96
Radstand (mm)	1145	1171	1197	1223
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	45	45	45	45
Stack (mm)	617	626	635	649
Reach (mm)	386	408	430	451
Überstandshöhe (mm)	753	760	787	791
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	60	60	70
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.