

REIGN ADVANCED 27.5 I



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Carbon / Metallic Green
RAHMEN	Advanced-Grade Composite front triangle, ALUXX SL Aluminum rear triangle
GABEL	DVO custom-tuned Diamond D2
DÄMPFER	DVO custom-tuned Topaz 2 T3
KOMPONENTEN	
LENKER	Giant Contact SL, 800x35mm, 20mm rise
VORBAU	Giant Contact SL 35, Diameter 35mm
SATTELSTÜTZE	Giant Contact Switch S dropper post with remote lever, 30.9mm
SATTEL	Contact SL (neutral)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle
BREMSEN	SRAM Code R [F] 200mm [R] 180mm, hydraulic disc
BREMSHEBEL	SRAM Code R
KASSETTE	SRAM XG-1275 Eagle, 10x50
KETTE	SRAM GX Eagle
KURBEL	TruVativ Descendent 6k, Eagle Dub, Boost, 32
LAUFRÄDER	
TRETLAGER	SRAM GXP Dub Press Fit
FELGEN	Giant TR 1 Hookless Alloy DBL WheelSystem
NABE	Giant TR 1 Hookless Alloy DBL WheelSystem, 28H
SPEICHEN	Giant TR 1 Hookless Alloy DBL WheelSystem
REIFEN	[F] Maxxis Minion DHF 27.5x2.5 WT, 60 tpi, 3C, EXO, TR [R] Maxxis Minion DHRII 27.5x2.4 WT, 60 tpi, 3C, EXO, TR, tubeless

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front triangle, ALUXX SL Aluminum rear triangle
- Gabel: DVO custom-tuned Diamond D2
- Schalthebel: SRAM GX Eagle, 1x12
- Kurbel: TruVativ Descendent 6k, Eagle Dub, Boost, 32
- Farbe: Carbon / Metallic Green

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	380	431	464	496
Sitzrohrwinkel	72.5°	72.5°	72.5°	72.5°
Oberrohrlänge (mm)	601	637	657	682
Steuerrohr-Länge (mm)	95	95	115	125
Steuerrohr-Winkel	64.5°	64.5°	64.5°	64.5°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	120	120	120	120
Radstand (mm)	1178	1213	1236	1262
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	7	7	7	7
Stack (mm)	580	580	599	608
Reach (mm)	419	454	469	491
Überstandshöhe (mm)	697.4	715.5	741.3	761.1
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	40	50	50	60
Kurbellänge (mm)	170	175	175	175
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.