



Spezifikationen

Rahmen	
Größen	XS, S, M, L
Farbe	Metallic Black / Neon Yellow / Black, Gray / Black / Neon Green
Rahmen	ALUXX-Grade Aluminum
Gabel	SR Suntour XCM RL 27.5, 100mm travel, remote lockout, with preload adjuster
Dämpfer	N/A
Komponenten	
Lenker	Giant Connect TR, 730mm x 31.8mm
Vorbau	Giant Sport, 6-degree
Sattelstütze	Giant Sport, 30.9x375mm
Sattel	Giant Connect (upright)
Pedale	MTB Caged, 9/16
Antrieb	
Schalthebel	Shimano Altus, 3x9
Umwirfer	Shimano Altus
Schaltwerk	Shimano Alivio
Bremsen	Tektro HDC M275 [F] 160 [R] 160, hydraulic
Bremshebel	Tektro HDC M275
Kassette	Shimano HG201-9, 11x36
Kette	KMC X9
Kurbel	ProWheel Burner, 22/32/44
Laufräder	
Tretlager	Feimin FP-902W
Felgen	Giant GX03V 27.5 6061 aluminum, double wall, 21mm inner width
Nabe	Giant Tracker Sport, 32H, [F] QR [R] QR
Speichen	stainless, 14G
Reifen	Maxxis Ikon, 60tpi wire, 27.5 x 2.2

Modell-Merkmale

- Rahmen: ALUXX-Grade Aluminum
- Gabel: SR Suntour XCM RL 27.5, 100mm travel, remote lockout, with preload adjuster
- Schalthebel: Shimano Altus, 3x9
- Kurbel: ProWheel Burner, 22/32/44
- Farbe: Metallic Black / Neon Yellow / Black, Gray / Black / Neon Green

Geometriedaten

Rahmen	XS	S	M	L	XL
Sitzrohlänge (mm)	350	390	430	490	535
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.5°	73.5°
Oberrohrlänge (mm)	545	570	595	615	640
Steuerrohr-Länge (mm)	100	115	130	155	170
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	42	42	42	42	42
Trail (mm)	98	98	98	98	98
Radstand (mm)	1072	1103	1128	1153	1179
Kettenstreben-Länge (mm)	440	440	440	440	440
Tretlager-Höhe (mm)	45	45	45	45	45
Stack (mm)	577	591	605	628	642
Reach (mm)	381	399	419	434	455
Überstandshöhe (mm)	690	714	749	788	823
Lenkerbreite (mm)	780	780	780	780	780
Vorbaulänge (mm)	40	50	60	70	80
Kurbellänge (mm)	170	170	175	175	175
Radgrösse	27.5"	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.