

TRANCE ADVANCED 27.5 1



SPEZIFIKATIONEN

| RAHMEN | |
|--------------|--|
| GRÖSSEN | S, M, L |
| FARBE | Carbon / Metallic Green |
| RAHMEN | Advanced-Grade Composite front triangle, ALUXX SL Aluminum rear triangle |
| GABEL | Fox 36 Float Performance Elite, 150mm travel, FIT4 Damper, Boost 15x110mm KaBolt, tapered steerer |
| DÄMPFER | Fox Float DPX2, Performance, trunnion mount |
| KOMPONENTEN | |
| LENKER | Giant Contact SL, 780x35mm, 20mm rise |
| VORBAU | Giant Contact SL 35 |
| SATTELSTÜTZE | Giant Contact Switch S dropper post with remote lever, 30.9mm |
| SATTEL | Contact SL (neutral) |
| PEDALE | N/A |
| ANTRIEB | |
| SCHALTHEBEL | SRAM GX Eagle, 1x12 |
| UMWERFER | N/A |
| SCHALTWERK | SRAM GX Eagle |
| BREMSEN | SRAM Guide RS [F] 180mm [R] 180mm, hydraulic disc |
| BREMSHEBEL | SRAM Guide RS |
| KASSETTE | SRAM XG-1275 Eagle, 10x50 |
| KETTE | SRAM GX Eagle |
| KURBEL | TruVativ Descendent 6k Eagle Dub, Boost, 32 |
| LAUFRÄDER | |
| TRETLAGER | SRAM GXP Dub Press Fit |
| FELGEN | Giant TRX 1 27.5 WheelSystem, hookless carbon, 30mm inner width |
| NABE | Giant TRX 1 27.5 WheelSystem |
| SPEICHEN | Giant TRX 1 27.5 WheelSystem |
| REIFEN | [F] Maxxis high Roller II 27.5x2.5 WT, 60 tpi, 3C, EXO, TR [R] Maxxis high Roller II 27.5x2.4, 60 tpi, 3C, EXO, TR, tubeless |

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front triangle, ALUXX SL Aluminum rear triangle
- Gabel: Fox 36 Float Performance Elite, 150mm travel, FIT4 Damper, Boost 15x110mm KaBolt, tapered steerer
- Schalthebel: SRAM GX Eagle, 1x12
- Kurbel: TruVativ Descendent 6k Eagle Dub, Boost, 32
- Farbe: Carbon / Metallic Green

GEOMETRIEDATEN

| RAHMEN | XS | S | M | L | XL |
|--------------------------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm) | 370 | 380 | 431 | 482 | 507 |
| Sitzrohrwinkel | 73.5° | 73.5° | 73.5° | 73.5° | 73.5° |
| Oberrohrlänge (mm) | 560 | 580 | 610 | 630 | 655 |
| Steuerrohr-Länge (mm) | 100 | 100 | 105 | 130 | 145 |
| Steuerrohr-Winkel | 67.0° | 67.0° | 67.0° | 67.0° | 67.0° |
| Gabelneigung (mm) | 42 | 42 | 42 | 42 | 42 |
| Trail (mm) | 104 | 104 | 104 | 104 | 104 |
| Radstand (mm) | 1109 | 1129 | 1160 | 1183 | 1209 |
| Kettenstreben-Länge (mm) | 435 | 435 | 435 | 435 | 435 |
| Tretlager-Höhe (mm) | 15 | 15 | 15 | 15 | 15 |
| Stack (mm) | 587 | 587 | 591 | 614 | 628 |
| Reach (mm) | 386 | 406 | 435 | 448 | 469 |
| Überstandshöhe (mm) | 697 | 701 | 723 | 768 | 788 |
| Lenkerbreite (mm) | 780 | 780 | 780 | 780 | 780 |
| Vorbaulänge (mm) | 40 | 50 | 50 | 50 | 60 |
| Kurbellänge (mm) | 170 | 170 | 175 | 175 | 175 |
| Radgrösse | 27.5" | 27.5" | 27.5" | 27.5" | 27.5" |

Spezifikations-, Preis- und Farbaenderungen vorbehalten.