

EXPLORE E+ 2 GTS



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Matte Black / Red
RAHMEN	ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
GABEL	RST Volante TNL coil, 60mm travel, tapered steerer, hydraulic lockout
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect XC Riser 31.8x690mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Selle Royal Vivo GTS/WMN
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano SL-M2000
UMWERFER	Shimano FD-M371
SCHALTWERK	Shimano Deore
BREMSEN	Shimano BR-MT200, hydraulic disc, 180mm
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano CS-HG200, 11-36T, 9-Speed
KETTE	KMC e.9 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36/48T
LAUFRÄDER	
TRETLAGER	N/A
FELGEN	Giant eX2, Tubeless Ready, 700c aluminium
NABE	Giant eTracker, [F] 100x9mm QR [R] 135mm QR
SPEICHEN	Stainless steel
REIFEN	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex
EXTRAS	Giant EnergyPak 4A fast charger MIK system carrier top-deck
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl Charge
BATTERY	Giant EnergyPak 500, 36V 13.8Ah Rechargeable Lithium-Ion
ACCESSORIES	
LIGHTING	Axa BlueLine 30Lux Steady E6 front Axa BlueLine Steady E6 rear
LOCK	-
GEPÄCKTRÄGER	MIK rack. System bag & basket compatible

MODELL-MERKMALE

- Rahmen: ALUXX SL aluminum, Overdrive 1½ - 1⅝" head tube, integrated KS18 kickstand mount
- Gabel: RST Volante TNL coil, 60mm travel, tapered steerer, hydraulic lockout
- Schalthebel: Shimano SL-M2000
- Kurbel: Forged Alloy minimal Q-factor, 36/48T
- Farbe: Matte Black / Red

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	435	485	535	585
Sitzrohrwinkel	74.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	570	590	610	630
Steuerrohr-Länge (mm)	130	140	155	170
Steuerrohr-Winkel	69.5°	69.5°	69.5°	69.5°
Gabelneigung (mm)	42	42	42	42
Trail (mm)	91.3	91.3	91.3	91.3
Radstand (mm)	1112	1121	1142	1163
Kettenstreben-Länge (mm)	455	455	455	455
Tretlager-Höhe (mm)	60	60	60	60
Stack (mm)	610	619	633	648
Reach (mm)	395	400	416	432
Überstandshöhe (mm)	745	775	808	844
Lenkerbreite (mm)	690	690	690	690
Vorbaulänge (mm)	60	70	80	90
Kurbellänge (mm)	170	170	170	170
Radgrösse	700c	700c	700c	700c

Spezifikations-, Preis- und Farbaenderungen vorbehalten.