REIGN ADVANCED PRO 29 2

SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Metallic Blue
RAHMEN	Advanced-Grade Composite front and rear triangles, 146mm
GABEL	RockShox Lyrik Select, 160mm, Boost 15x110 Maxle Stealth, tapered, 42mm offset
DÄMPFER	RockShox Deluxe select+
KOMPONENTEN	
LENKER	Giant Contact TR35, 800x35mm, 20mm rise
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch dropper post with remote, 30.9
SATTEL	Giant Contact (neutral)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM NX Eagle
UMWERFER	N/A
SCHALTWERK	SRAM NX Eagle
BREMSEN	Shimano MT520
BREMSHEBEL	Shimano MT501
KASSETTE	SRAM NX Eagle, 11x50
KETTE	SRAM NX Eagle
KURBEL	TruVativ Descendent 6k DUB, 32t with MRP AMg CS guide
LAUFRÄDER	
TRETLAGER	SRAM DUB, press fit
FELGEN	Giant AM 29, tubeless ready sleeve-joint rim, 30mm inner width
NABE	[F] Giant Tracker Performance Boost 15x110, sealed bearing [R] Giant Tracker Performance Boost 12x148, sealed bearing
SPEICHEN	Sapim
REIFEN	[F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Minion DHR II 29x2.4 WT, EXO, TR, tubeless
EXTRAS	Tubeless prepared

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 146mm
- Gabel: RockShox Lyrik Select, 160mm, Boost 15x110 Maxle Stealth, tapered, 42mm offset
- Schalthebel: SRAM NX Eagle
- Kurbel: TruVativ Descendent 6k DUB, 32t with MRP AMg CS guide
- Farbe: Metallic Blue

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	431	431	464	496
Sitzrohrwinkel	76.8°	76.8°	76.8°	76.8°
Oberrohrlänge (mm)	573	600	640	665
Steuerrohr-Länge (mm)	100	110	110	120
Steuerrohr-Winkel	65.0°	65.0°	65.0°	65.0°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	128.9	128.9	128.9	128.9
Radstand (mm)	1188	1215	1258	1265
Kettenstreben-Länge (mm)	439	439	439	439
Tretlager-Höhe (mm)	30	30	30	30
Stack (mm)	619	619	628	637
Reach (mm)	428	455	493	516
Überstandshöhe (mm)	752	751	773	788
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	40	40	40	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.