



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Metallic Navy
RAHMEN	ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
GABEL	RockShox Recon RL, 130mm travel, Lockout, 110x15mm MaxleLite
DÄMPFER	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (S:100/M:125/L:150/XL:170)
SATTEL	Giant Contact, Neutral
PEDALE	-
ANTRIEB	
SCHALTHEBEL	SRAM SX Eagle 12-speed
UMWERFER	-
SCHALTWERK	SRAM SX Eagle 12-speed
BREMSEN	Shimano MT520, 4-piston brakes, 203mm
BREMSHEBEL	Shimano MT501 Hydraulic Disc
KASSETTE	SRAM PG-1210, 11-50T, 12-Speed
KETTE	SRAM SX Eagle PowerLock, 12-speed
KURBEL	SRAM X-Sync Eagle 38T 104BCD chainring Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
LAUFRÄDER	
TRETLAGER	N/A
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle
SPEICHEN	Sapim E-Lite [r] Race [f], e-bike optimized
REIFEN	Maxxis Ardent 29x2.4" foldable, 60tpi Dual Compound EXO, Tubeless Ready
EXTRAS	Giant EnergyPak 6A Smart charger Tubeless kit (liquid, valves, levelrs, manual, tool)
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro
SENSORS	Giant PedalPlus 6-sensor technology
DISPLAY	Giant RideControl ONE
BATTERY	Giant EnergyPak Smart 500, 36V 13.8Ah integrated Lithium-Ion

MODELL-MERKMALE

- Rahmen: ALUXX SL-grade aluminum, 120mm FlexPoint suspension system
- Gabel: RockShox Recon RL, 130mm travel, Lockout, 110x15mm MaxleLite
- Schalthebel: SRAM SX Eagle 12-speed
- Kurbel: SRAM X-Sync Eagle 38T 104BCD chainring Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
- Farbe: Metallic Navy

GEOMETRIEDATEN

RAHMEN	XS	S	M	L	XL
Sitzrohrlänge (mm)	380	406	432	482	507
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.5°	73.5°
Oberrohrlänge (mm)	565	580	600	625	650
Steuerrohr-Länge (mm)	100	100	110	120	135
Steuerrohr-Winkel	67.0°	67.0°	67.0°	67.0°	67.0°
Gabelneigung (mm)	51	51	51	51	51
Trail (mm)	106.9	106.9	106.9	106.9	106.9
Radstand (mm)	1147	1162	1183	1209	1236
Kettenstreben-Länge (mm)	465	465	465	465	465
Tretlager-Höhe (mm)	20	20	20	20	20
Stack (mm)	590	590	599	608	622
Reach (mm)	390	405	422	444	465
Überstandshöhe (mm)	715	731	746	778	781
Lenkerbreite (mm)	780	780	780	780	780
Vorbaulänge (mm)	50	50	50	50	60
Kurbellänge (mm)	160	160	165	165	170
Radgrösse	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.