

TCR ADVANCED SL 1 DISC FORCE



SPEZIFIKATIONEN

| RAHMEN | |
|--------------|---|
| GRÖSSEN | XS, S, M, ML, L, XL |
| FARBE | Metallic Navy / Iris |
| RAHMEN | Advanced SL-Grade Composite, integrated seatpost, disc |
| GABEL | Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc |
| DÄMPFER | N/A |
| KOMPONENTEN | |
| LENKER | Giant Contact SLR |
| VORBAU | Giant Contact SLR |
| SATTELSTÜTZE | integrated design |
| SATTEL | Giant Contact SLR (forward) |
| PEDALE | N/A |
| ANTRIEB | |
| SCHALTHEBEL | SRAM Force eTap AXS |
| UMWERFER | SRAM Force eTap AXS |
| SCHALTWERK | SRAM Force eTap AXS |
| BREMSEN | SRAM Force eTap AXS hydraulic |
| BREMSHEBEL | SRAM Force eTap AXS hydraulic |
| KASSETTE | SRAM Force, 12-speed, 10x28 |
| KETTE | SRAM Force D1 |
| KURBEL | SRAM Force D1 DUB, 35/48 with Quarq DZero power meter |
| LAUFRÄDER | |
| TRETLAGER | SRAM DUB, press fit |
| FELGEN | Giant SLR-1 Disc Composite WheelSystem (F:42mm, R:42mm) |
| NABE | Giant SLR-1 Disc WheelSystem, 12mm thru-axle |
| SPEICHEN | Giant SLR-1 Disc WheelSystem |
| REIFEN | CADEX Race 25, tubeless, 700x25, folding |
| EXTRAS | RideSense Bluetooth |

MODELL-MERKMALE

- Rahmen: Advanced SL-Grade Composite, integrated seatpost, disc
- Gabel: Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
- Schalthebel: SRAM Force eTap AXS
- Kurbel: SRAM Force D1 DUB, 35/48 with Quarq DZero power meter
- Farbe: Metallic Navy / Iris

GEOMETRIEDATEN

| RAHMEN | XS | S | M | ML | L | XL |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm) | 680 | 710 | 740 | 770 | 790 | 820 |
| Sitzrohrwinkel | 74.5° | 73.5° | 73.0° | 73.0° | 73.0° | 72.0° |
| Oberrohrlänge (mm) | 515 | 535 | 550 | 570 | 580 | 605 |
| Steuerrrohr-Länge (mm) | 123 | 133 | 148 | 168 | 188 | 203 |
| Steuerrrohr-Winkel | 71.0° | 72.5° | 73.0° | 73.0° | 73.0° | 73.0° |
| Gabelneigung (mm) | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 69.8 | 60.3 | 57.2 | 57.2 | 57.2 | 57.2 |
| Radstand (mm) | 972 | 970 | 976 | 997 | 1007 | 1021 |
| Kettenstreben-Länge (mm) | 405 | 405 | 405 | 405 | 405 | 405 |
| Tretlager-Höhe (mm) | 70 | 68 | 68 | 65 | 65 | 65 |
| Stack (mm) | 517 | 529 | 545 | 562 | 581 | 595 |
| Reach (mm) | 372 | 378 | 383 | 398 | 402 | 412 |
| Überstandshöhe (mm) | 724 | 742 | 765 | 787 | 805 | 823 |
| Lenkerbreite (mm) | 400 | 400 | 420 | 420 | 440 | 440 |
| Vorbaulänge (mm) | 80 | 90 | 100 | 110 | 110 | 120 |
| Kurbellänge (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 |
| Radgrösse | 700C | 700C | 700C | 700C | 700C | 700C |

Spezifikations-, Preis- und Farbaenderungen vorbehalten.