



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Metallic Black
RAHMEN	ALUXX SLR-Grade Aluminum, disc
GABEL	Advanced-Grade Composite, alloy OverDrive steerer, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XC, 31.8
VORBAU	Giant Contact, 8-degree
SATTELSTÜTZE	Giant D-Fuse, composite
SATTEL	Giant Contact Comfort (neutral)
PEDALE	platform
ANTRIEB	
SCHALTHEBEL	Shimano XT
UMWERFER	microSHIFT XLE
SCHALTWERK	Shimano Deore XT
BREMSEN	TRP Slate T4
BREMSHEBEL	TRP Slate T4
KASSETTE	Shimano CS-M7000, 11x42
KETTE	KMC X11-EL
KURBEL	FSA V-Drive, 32/44 with chainguard
LAUFRÄDER	
TRETLAGER	FSA MegaExo
FELGEN	Giant P-X2 wheelset
NABE	Giant P-X2 wheelset
SPEICHEN	Giant P-X2 wheelset
REIFEN	Giant Sycamore S, 700x50, FlatGuard Deflect 2
EXTRAS	X-Defender protection

MODELL-MERKMALE

- Rahmen: ALUXX SLR-Grade Aluminum, disc
- Gabel: Advanced-Grade Composite, alloy OverDrive steerer, disc
- Schalthebel: Shimano XT
- Kurbel: FSA V-Drive, 32/44 with chainguard
- Farbe: Metallic Black

GEOMETRIEDATEN

RAHMEN	XS	S	M	L	XL
Sitzrohlänge (mm)	390	420	460	510	550
Sitzrohrwinkel	73.0°	73.0°	73.0°	72.0°	71.5°
Oberrohrlänge (mm)	580	585	595	605	620
Steuerrohr-Länge (mm)	100	125	150	170	190
Steuerrohr-Winkel	71.5°	71.5°	71.5°	72.0°	72.0°
Gabelneigung (mm)	42	42	42	42	42
Trail (mm)	78.3	78.3	78.3	74.9	74.9
Radstand (mm)	1061	1067	1078	1071	1080
Kettenstreben-Länge (mm)	450	450	450	450	450
Tretlager-Höhe (mm)	70	70	70	70	70
Stack (mm)	555	578	602	623	642
Reach (mm)	410	408	411	403	405
Überstandshöhe (mm)	696	724	754	795	864
Lenkerbreite (mm)	640	640	640	690	690
Vorbaulänge (mm)	80	90	100	110	110
Kurbellänge (mm)	165	170	175	175	175
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbaenderungen vorbehalten.