

TRANCE ADVANCED PRO 29 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Copper
RAHMEN	Advanced-Grade Composite front and rear triangles, 115mm
GABEL	Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110 QR, tapered
DÄMPFER	Fox Float DPS Performance
KOMPONENTEN	
LENKER	Giant Contact TR35, 780x35mm, 20mm rise
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch dropper with remote, 30.9
SATTEL	Giant Contact (neutral)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM NX Eagle
UMWERFER	N/A
SCHALTWERK	SRAM NX Eagle
BREMSEN	SRAM guide T
BREMSHEBEL	SRAM guide T
KASSETTE	SRAM NX Eagle, 11x50
KETTE	SRAM NX Eagle
KURBEL	TruVativ Descendent 6k DUB, 30t
LAUFRÄDER	
TRETLAGER	SRAM DUB, press fit
FELGEN	Giant TRX-1 29 Composite WheelSystem
NABE	Giant TRX-1 29 WheelSystem
SPEICHEN	Giant TRX-1 29 WheelSystem
REIFEN	[F] Maxxis Minion DHF 29x2.3, EXO, TR [R] Maxxis DHR II 29x2.3, EXO, TR, tubeless

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 115mm
- Gabel: Fox 34 Rhythm, 130mm, GRIP damper, Boost 15x110 QR, tapered
- Schalthebel: SRAM NX Eagle
- Kurbel: TruVativ Descendent 6k DUB, 30t
- Farbe: Copper

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohlänge (mm)	380	431	464	496
Sitzrohrwinkel	74.5°	74.5°	74.5°	74.5°
Oberrohrlänge (mm)	592	612	632	652
Steuerrohr-Länge (mm)	95	110	110	120
Steuerrohr-Winkel	66.5°	66.5°	66.5°	66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	116.8	116.8	116.8	116.8
Radstand (mm)	1154	1176	1196	1218
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	35	35	35	35
Stack (mm)	599	613	613	622
Reach (mm)	426	442	462	480
Überstandshöhe (mm)	708	740	761	785
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	60
Kurbellänge (mm)	170	175	175	175
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.