



## SPEZIFIKATIONEN

### HYBRID CYCLING TECHNOLOGY

<b>MOTOR</b>	Giant SyncDrive Core
<b>SENSOR</b>	Giant RideControl Curve
<b>DISPLAY</b>	Giant RideControl EVO
<b>BATTERY</b>	Giant EnergyPak Smart 625Wh

### RAHMEN

<b>GRÖSSEN</b>	S, M, L, XL
<b>FARBE</b>	Metallic Navy

<b>RAHMEN</b>	ALUXXSL aluminum
<b>GABEL</b>	SR Suntour NEX E25, lockout, 63mm, 15AQ
<b>DÄMPFER</b>	N/A

### KOMPONENTEN

<b>LENKER</b>	Giant Contour GT, cable integrated, 30° back sweep 31.8mm
<b>VORBAU</b>	Giant Contour, EVO display integrated, adjustable
<b>SATTELSTÜTZE</b>	Suspension 2-bolt micro-adjustable, 30,9x270mm
<b>SATTEL</b>	Selle Royal Look-In gel
<b>PEDALE</b>	VP191 light weight aluminum

### ANTRIEB

<b>SCHALTHEBEL</b>	Shimano Nexus 8speed REVOSHIFT
<b>UMWERFER</b>	-
<b>SCHALTWERK</b>	-
<b>BREMSEN</b>	Shimano MT201 Hydraulic Disc
<b>BREMSHEBEL</b>	Shimano MT201 Hydraulic Disc
<b>KASSETTE</b>	Gates CDXtm stainless steel 26T rear sprocket
<b>KETTE</b>	Gates CDXtm Carbon Drive 120T CenterTrack belt
<b>KURBEL</b>	Gates CDXtm CenterTrack 46T front sprocket
<b>TRETLAGER</b>	N/A

### LAUFRÄDER

<b>FELGEN</b>	Giant eX2, Tubeless Ready, 700c Aluminium
<b>NABE</b>	Shimano HB-MT400 100x15mm thru-axle Disc [F]Shimano Nexus 8 Disc brake [R]
<b>SPEICHEN</b>	Sapim Race [F], Sapim Strong [R]
<b>REIFEN</b>	Schwalbe Marathon E Plus 622x50, Smart DualGuard Addix E
<b>EXTRAS</b>	Giant EnergyPak 6A Smart charger

### ACCESSORIES

<b>LIGHTING</b>	Giant Numen iD integrated day-time LED Axa Blueline 30 automatic front LEDAxa Blueline rear LED
<b>LOCK</b>	Abus Pro Shield 5850 ART approved

## MODELL-MERKMALE

- Rahmen: ALUXX SL aluminum
- Gabel: SR Suntour NEX E25, lockout, 63mm, 15AQ
- Schalthebel: Shimano Nexus 8speed REVOSHIFT
- Kurbel: Gates CDXtm CenterTrack 46T front sprocket
- Farbe: Metallic Navy

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL	XXL
Sitzrohrwinkel	72.5°	72.0°	72.0°	72.0°	72.0°
Oberrohrlänge (mm)	580	590	610	630	645
Steuerrohr-Länge (mm)	145	160	170	185	200
Steuerrohr-Winkel	69.5°	69.5°	69.5°	69.5°	69.5°
Radstand (mm)	1107	1112	1132	1153	1153
Kettenstreben-Länge (mm)	470	470	470	470	470
Stack (mm)	620	634	643	657	657
Reach (mm)	384	384	401	416	416
Überstandshöhe (mm)	743	776	818	855	854.8
Kurbellänge (mm)	170	170	170	170	170

Spezifikations-, Preis- und Farbaenderungen vorbehalten.