



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Sport
DISPLAY	Giant RideControl Plus (optional)
BATTERY	Giant EnergyPak Smart 500, 36V Integrated Lithium-Ion
RAHMEN	
GRÖSSEN	S, M, L, XL, XXL
FARBE	Gunmetal Black Color B: Desert Sage
RAHMEN	ALUXX Aluminum, Overdrive 1½ - 1⅝" Head Tube, 141mm Boost QR, ISS, Giant EnergyPak Plus Range Extender Compatible, Integrated KS18 Kickstand Mount
GABEL	SR Suntour XCR 32 Boost Coil LOR 29 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x690-780mm
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	-
SCHALTWERK	Shimano Deore, 10-Speed, Shadow+
BREMSEN	Shimano BR-MT200, hydraulic disc, 180mm [F&R]
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano CS-M4100-10 11-46T 10-Speed
KETTE	KMC e.10 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36T Steel Direct Mount
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR, e-bike optimized
SPEICHEN	Stainless steel
REIFEN	Maxxis Rekon 29x2.4", EXO, 60 TPI
EXTRAS	Giant EnergyPak 6A Smart charger Giant EnergyPak Plus range extender compatible

MODELL-MERKMALE

- Rahmen: ALUXX Aluminum, Overdrive 1½ - 1⅝" Head Tube, 141mm Boost QR, ISS, Giant EnergyPak Plus Range Extender Compatible, Integrated KS18 Kickstand Mount
- Gabel: SR Suntour XCR 32 Boost Coil LOR 29 120mm travel, Tapered 1½ - 1⅝" steerer, lockout
- Schalthebel: Shimano Deore
- Kurbel: Forged Alloy minimal Q-factor, 36T Steel Direct Mount
- Farbe: Gunmetal Black Color B: Desert Sage

GEOMETRIEDATEN

RAHMEN	XS	S	M	L	XL	XXL
Sitzrohrlänge (mm)	365	405	455	505	535	560
Sitzrohrwinkel	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	560	575	600	625	650	675
Steuerrohr-Länge (mm)	105	105	115	125	140	155
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	46	46	46	46	46	46
Trail (mm)	100.7	100.7	100.7	100.7	100.7	101
Radstand (mm)	1126	1141	1167	1193	1219	1245
Kettenstreben-Länge (mm)	475	475	475	475	475	475
Tretlager-Höhe (mm)	45	45	45	45	45	45
Stack (mm)	625	625	634	643	657	671
Reach (mm)	369	384	406	428	449	470
Überstandshöhe (mm)	702	723	753	788	808	828
Lenkerbreite (mm)	780	780	780	780	780	780
Vorbaulänge (mm)	40	50	60	60	70	70
Kurbellänge (mm)	160	165	170	170	170	170
Radgrösse	29"	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.