

EXPLORE E+ 1 GTS



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport, 70Nm, powered by Yamaha
SENSOR	RideControl Ergo
DISPLAY	RideDash Evo
BATTERY	EnergyPak Smart 625Wh EnergyPak Plus range extender compatible
RAHMEN	
GRÖSSEN	S, M, L, XL, XXL
FARBE	Gunmetal Black
RAHMEN	ALUXX Aluminum, Overdrive 1½ - 1⅞" head tube, integrated KS18 kickstand mount
GABEL	SR Suntour NEX E25 NLO 63mm travel 15AH
DÄMPFER	-
KOMPONENTEN	
LENKER	Giant Connect XC Riser 31.8x690mm
GRIPS	Giant Contact Ergo Max Plus
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Selle Royal Vivo Ergo Moderate
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	Shimano Deore
SCHALTWERK	Shimano Deore, 10-speed, Shadow+
BREMSEN	Shimano BR-MT200, hydraulic disc, 180mm
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano CS-M4100, 11-42T, 10-speed
KETTE	KMC e.10 Sport, e-bike optimized
KURBEL	Forged Alloy minimal Q-factor, 36/48T
TRETLAGER	-
LAUFRÄDER	
FELGEN	Giant eX 2, Tubeless Ready, 700c Aluminium
NABE	Giant eTracker, [F] 15mm Axle [R] 135mm QR
SPEICHEN	Stainless steel
REIFEN	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex
ACCESSORIES	
LIGHTING	Axa BlueLine 50Lux Steady E6 frontAxa BlueLine Steady E6 rear
GEPÄCKTRÄGER	MIK rack. System bag & basket compatible

MODELL-MERKMALE

- Rahmen: ALUXX Aluminum, Overdrive 1½ - 1⅞" head tube, integrated KS18 kickstand mount
- Gabel: SR Suntour NEX E25 NLO 63mm travel 15AH
- Schalthebel: Shimano Deore
- Kurbel: Forged Alloy minimal Q-factor, 36/48T
- Farbe: Gunmetal Black

GEOMETRIEDATEN

RAHMEN	S	M	L	XL	XXL
Sitzrohrlänge (mm)	435	485	535	585	610
Sitzrohrwinkel	74.0°	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	570	590	610	630	650
Steuerrohr-Länge (mm)	130	140	155	170	185
Steuerrohr-Winkel	69.5°	69.5°	69.5°	69.5°	69.5°
Gabelneigung (mm)	42	42	42	42	42
Trail (mm)	91.3	91.3	91.3	91.3	91.3
Radstand (mm)	1112	1121	1142	1163	1163
Kettenstreben-Länge (mm)	455	455	455	455	455
Tretlager-Höhe (mm)	60	60	60	60	60
Stack (mm)	610	619	633	648	648
Reach (mm)	395	400	416	432	432
Überstandshöhe (mm)	745	775	808	844	844
Lenkerbreite (mm)	690	690	690	690	690
Vorbaulänge (mm)	60	70	80	90	90
Kurbellänge (mm)	170	170	170	170	170
Radgrösse	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbaenderungen vorbehalten.