



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport, 70Nm Powered by Yamaha
SENSOR	RideControl Dash, full color LCD screen
DISPLAY	RideControl Dash, full color LCD screen
BATTERY	EnergyPak Smart 500, 36V Integrated Lithium-IonEnergyPak Plus range extender compatible
RAHMEN	
GRÖSSEN	S, M, L, XL, XXL
FARBE	Color A: Black, Color B: Metallic Blue
RAHMEN	ALUXX Aluminum, Overdrive 1½ - 1¼" Head Tube, 141mm Boost QR, ISS, Giant EnergyPak Plus Range Extender Compatible, Integrated KS18 Kickstand Mount
GABEL	SR Suntour XCR 32 Coil LO Boost 29 120mm travel, Tapered 1½ - 1¼" steerer, lockout
DÄMPFER	-
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Sole-O Grip
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	-
SCHALTWERK	Shimano Deore, 10-speed, Shadow+
BREMSEN	Tektro HD-M280, hydraulic disc, 180mm
BREMSHEBEL	Shimano BL-MT200
KASSETTE	Shimano CS-M4100-10 11-46T 10-speed
KETTE	KMC e.10 Sport, e-bike optimized
KURBEL	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
TRETLAGER	N/A
LAUFRÄDER	
FELGEN	Giant XCT 29 Tubeless Ready 25mm e-bike optimized
NABE	Shimano HB-MT401-B front , Shimano FH-MT200-B rear
SPEICHEN	Stainless steel
REIFEN	Maxxis Rekon 29x2.4", EXO, 60 TPI
ACCESSORIES	
LIGHTING	-
GEPÄCKTRÄGER	-

MODELL-MERKMALE

- Rahmen: ALUXX Aluminum, Overdrive 1½ - 1¼" Head Tube, 141mm Boost QR, ISS, Giant EnergyPak Plus Range Extender Compatible, Integrated KS18 Kickstand Mount
- Gabel: SR Suntour XCR 32 Coil LO Boost 29 120mm travel, Tapered 1½ - 1¼" steerer, lockout
- Schalthebel: Shimano Deore
- Kurbel: FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
- Farbe: Color A: Black, Color B: Metallic Blue

GEOMETRIEDATEN

RAHMEN	S	M	L	XL	XXL
Sitzrohrlänge (mm)	405	455	505	535	560
Sitzrohrwinkel	73.0°	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	575	600	625	650	675
Steuerrohr-Länge (mm)	105	115	125	140	155
Steuerrohr-Winkel	68.0°	68.0°	68.0°	68.0°	68.0°
Gabelneigung (mm)	46	46	46	46	46
Trail (mm)	100.7	100.7	100.7	100.7	101
Radstand (mm)	1141	1167	1193	1219	1245
Kettenstreben-Länge (mm)	475	475	475	475	475
Tretlager-Höhe (mm)	45	45	45	45	45
Stack (mm)	625	634	643	657	671
Reach (mm)	384	406	428	449	470
Überstandshöhe (mm)	723	753	788	808	828
Lenkerbreite (mm)	690	750	750	780	780
Vorbaulänge (mm)	50	60	60	70	70
Kurbellänge (mm)	160	165	170	170	170
Radgrösse	29"	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.