



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 80Nm, powered by Yamaha
SENSOR	RideControl Dash, full color LCD screen
DISPLAY	RideControl Dash, full color LCD screen
BATTERY	EnergyPak Smart 625Wh EnergyPak Plus range extender compatible
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Gunmetal Black
RAHMEN	ALUXX Aluminum, Overdrive 1½ - 1¼" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
GABEL	SR Suntour XCR 34 Boost Air LOR, 130mm travel, Tapered 1½ - 1¼" steerer, lockout
DÄMPFER	-
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal Lock-On
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore LinkGlide
UMWERFER	-
SCHALTWERK	Shimano Deore, 10-speed, LinkGlide, Shadow+
BREMSEN	Tektro HD-M275, hydraulic disc, 180mm [F/R]
BREMSHEBEL	Tektro HD-M275
KASSETTE	Shimano Deore LinkGlide CS-M5130-10, 11-43T, 10-speed
KETTE	Shimano, CN-LG500, 9/10/11speed for LinkGlide
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
TRETLAGER	-
LAUFRÄDER	
FELGEN	Giant AM 29", Tubeless ready, 30mm inner width
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Stainless steel
REIFEN	Maxxis Minion DHF 29X2.5" 60TPI Foldable, TLR EXO [F] Maxxis Aggressor 29X2.5" 60TPI Foldable TLR EXO [R]
ACCESSORIES	
LIGHTING	-

## MODELL-MERKMALE

- Rahmen: ALUXX Aluminum, Overdrive 1½ - 1¼" head tube, 148x12mm Thru-Axle, integrated KS18 kickstand mount
- Gabel: SR Suntour XCR 34 Boost Air LOR, 130mm travel, Tapered 1½ - 1¼" steerer, lockout
- Schalthebel: Shimano Deore LinkGlide
- Kurbel: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set
- Farbe: Gunmetal Black

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	405	455	505	535
Sitzrohrwinkel	76.0°	76.0°	76.0°	76.0°
Oberrohrlänge (mm)	575	600	625	650
Steuerrohr-Länge (mm)	105	115	125	135
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	51	51	51	51
Trail (mm)	108.5	108.5	108.5	108.5
Radstand (mm)	1204	1231	1258	1285
Kettenstreden-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	45	45	45	45
Stack (mm)	616	625	635	644
Reach (mm)	421	444	467	490
Überstandshöhe (mm)	758	762	794	816
Lenkerbreite (mm)	780	780	780	780
Vorbauhöhe (mm)	50	60	60	70
Kurbellänge (mm)	160	165	165	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.