



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Amber Glow / Rainbow Black
RAHMEN	Advanced-Grade Composite front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
GABEL	Fox 38 Factory Live Valve, 170mm, FIT4 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
DÄMPFER	Fox Factory Live Valve, 205/60, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SLR TR35, composite, 800x35mm, 20mm rise
GRIPS	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:40mm, XL:40mm
SATTELSTÜTZE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm L: 170-200mm travel / 30.9 x 525mm XL: 170-200mm travel / 30.9 x 525mm
SATTEL	Giant Romero SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle
BREMSEN	Shimano SLX M7120, hydraulic, Shimano RT-66 rotors [F]203mm, [R]203mm
BREMSHEBEL	Shimano SLX BL-M7100
KASSETTE	SRAM XG-1275 Eagle, 10x52
KETTE	SRAM GX Eagle
KURBEL	TruVativ Descendent 6k, DUB, 32t S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM DUB, press fit
LAUFRÄDER	
FELGEN	Giant TRX 2 29 WheelSystem
NABE	Giant TRX 2 29 WheelSystem
SPEICHEN	Giant TRX 2 29 WheelSystem
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxTerra, EXO+, TR [R] Maxxis Minion DHR II 29x2.4 WT, 3C MaxxTerra , EXO+, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP AMG CS chain guide, 3M tailgate protector

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 146mm Maestro suspension, 12x148mm thru-axle
- Gabel: Fox 38 Factory Live Valve, 170mm, FIT4 damper, 15x110 Kabolt X, 44mm offset, custom tuned for Giant
- Schalthebel: SRAM GX Eagle, 1x12
- Kurbel: TruVativ Descendent 6k, DUB, 32t S:165mm, M:170mm, L:170mm, XL:170mm
- Farbe: Amber Glow / Rainbow Black

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	431	431	464	496
Sitzrohrwinkel	76.4°	76.4°	76.4°	76.4°
Oberrohrlänge (mm)	574	601	640	666
Steuerrohr-Länge (mm)	100	100	110	120
Steuerrohr-Winkel	64.6°	64.6°	64.6°	64.6°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	132.7	132.7	132.7	132.7
Radstand (mm)	1191	1220	1262	1289
Kettenstreben-Länge (mm)	439	439	439	439
Tretlager-Höhe (mm)	27	27	27	27
Stack (mm)	622	622	631	640
Reach (mm)	423	451	488	511
Überstandshöhe (mm)	757	759	781	804
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	40	40	40	40
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.