



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Phantom Green
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant Contact Switch, dropper, 30.9mm XS:295mm, S:345mm, M:345mm, M/L:345mm, L:395mm, XL:395mm
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM Rival eTap AXS, 2x12
UMWERFER	N/A
SCHALTWERK	SRAM Rival eTap AXS XPLR
BREMSEN	SRAM Rival eTap AXS hydraulic, Giant MPH rotors [F]160mm, [R]140mm
BREMSEBEL	SRAM Rival eTap AXS hydraulic
KASSETTE	SRAM Rival, 12-speed, 10x44
KETTE	SRAM Rival D1
KURBEL	SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit
LAUFRÄDER	
FELGEN	Giant P-X2 Disc wheelset
NABE	Giant P-X2 Disc wheelset
SPEICHEN	Giant P-X2 Disc wheelset
REIFEN	Maxxis Rambler, 700x45c, tubeless
EXTRAS	Giant 1x chain guide, tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
- Gabel: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Schalthebel: SRAM Rival eTap AXS, 2x12
- Kurbel: SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farbe: Phantom Green

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG	SHORT LONG
Sitzrohlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600
Steuerrohr-Länge (mm)	125	135	150	165	180	195
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68
Radstand (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051 1061
Kettenstreben-Länge (mm)	425 435	425 435	425 435	425 435	425 435	425 435
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Überstandshöhe (mm)	724 731	740 747	757 764	774 780	791 797	807 814
Lenkerbreite (mm)	420	420	440	440	460	460
Vorbaulänge (mm)	50	60	70	80	80	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.