



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Matte Carbon / Gloss Black
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SLR XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIPS	Stratus Lite 3.0
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse SLR, composite, -5/+15mm offset
SATTEL	Giant Approach SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM Rival eTap AXS, 2x12
UMWERFER	SRAM Rival eTap AXS
SCHALTWERK	SRAM Rival eTap AXS
BREMSEN	SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm
BREMSHEBEL	SRAM Rival eTap AXS hydraulic
KASSETTE	SRAM Rival, 12-speed, 10x33
KETTE	SRAM Rival D1
KURBEL	SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit
LAUFRÄDER	
FELGEN	Giant CXR 1 Carbon Disc WheelSystem
NABE	Giant CXR 1 Carbon Disc WheelSystem
SPEICHEN	Giant CXR 1 Carbon Disc WheelSystem
REIFEN	Maxxis Receptor, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 42mm max tire size in "short" flip chip position

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
- Gabel: Advanced SL-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Schalthebel: SRAM Rival eTap AXS, 2x12
- Kurbel: SRAM Rival D1 DUB, 30/43 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farbe: Matte Carbon / Gloss Black

GEOMETRIEDATEN

RAHMEN	XS						XL
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT
Sitzrohlänge (mm)	430	450	470	490	510	530	550
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600	610
Steuerrohr-Länge (mm)	125	135	150	165	180	195	210
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65 68	65 68
Radstand (mm)	1024 1034	1020 1030	1026 1036	1031 1041	1041 1051	1051 1061	1061 1071
Kettenstreben-Länge (mm)	425 435	425 435	425 435	425 435	425 435	425 435	425 435
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	586	602	616	630	644
Reach (mm)	381	381	387	391	397	407	417
Überstandshöhe (mm)	724 731	740 747	757 764	774 780	791 797	807 813	823 829
Lenkerbreite (mm)	420	420	440	440	460	460	460
Vorbaulänge (mm)	50	60	70	80	80	90	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175	175
Radgrösse	700C	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.