



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Rosewood
RAHMEN	ALUXX-Grade Aluminum, 120mm FlexPoint suspension
GABEL	Crest 34 SL RCL, 130mm, Boost 15x110 QR, custom tuned for Giant
DÄMPFER	RockShox Monarch R, 184.15/44.45, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Connect Trail, 780x31.8mm
GRIPS	Giant Sole-O
VORBAU	Giant Contact S:50mm, M:50mm, L:60mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch dropper, remote S: 100mm travel / 30.9 x 345mm M: 125mm travel / 30.9 x 395mm L: 150mm travel / 30.9 x 440mm XL: 150mm travel / 30.9 x 440mm
SATTEL	Giant Romero
PEDALE	platform [GC,GT]
ANTRIEB	
SCHALTHEBEL	SRAM SX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM SX Eagle
BREMSEN	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano BL-MT401
KASSETTE	SRAM SX Eagle, 11x50
KETTE	SRAM SX Eagle
KURBEL	SRAM SX Eagle DUB, 30t S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM DUB, press fit
LAUFRÄDER	
FELGEN	Giant AM 29 alloy, tubeless ready
NABE	[F] Giant Tracker Performance Boost 15x110, sealed bearing [R] Giant Tracker Giant Sport QR141, loose ball
SPEICHEN	Sapim
REIFEN	Maxxis Forekaster 29x2.35, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.4", max chainring size 32t

MODELL-MERKMALE

- Rahmen: ALUXX-Grade Aluminum, 120mm FlexPoint suspension
- Gabel: Crest 34 SL RCL, 130mm, Boost 15x110 QR, custom tuned for Giant
- Schalthebel: SRAM SX Eagle, 1x12
- Kurbel: SRAM SX Eagle DUB, 30t S:165mm, M:170mm, L:170mm, XL:170mm
- Farbe: Rosewood

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	380	431	482	507
Sitzrohrwinkel	75.0°	75.0°	75.0°	75.0°
Oberrohrlänge (mm)	570	593	624	645
Steuerrohr-Länge (mm)	100	100	125	140
Steuerrohr-Winkel	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	100.1	100.1	100.1	100.1
Radstand (mm)	1134	1157	1192	1215
Kettenstreben-Länge (mm)	438	438	438	438
Tretlager-Höhe (mm)	40	40	40	40
Stack (mm)	612	612	635	668
Reach (mm)	406	429	454	471
Überstandshöhe (mm)	730	734	763	782
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	50	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.