



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 80Nm, powered by Yamaha
SENSOR	RideControl Dash, full color LCD screen
DISPLAY	RideControl Dash, full color LCD screen
BATTERY	EnergyPak Smart 625Wh
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Phantom Green
RAHMEN	ALUXX Aaluminum, 120mm FlexPoint suspension system
GABEL	RockShox Recon Silver RL,130mm travel, Lock-out, Tapered Steerer,15x110mm Boost, MaxleLite, e-MTB optimized
DÄMPFER	RockShox Monarch RT, High Volume, 184x44mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
GRIPS	Giant Tactal single lock-on
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (S:100/M:125/L:150/XL:170)
SATTEL	Giant Romero Trail
PEDALE	Flatpedal
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	MRP 1X custom "V3" co-molded TR chain guide
SCHALTWERK	Shimano Deore 12-speed
BREMSEN	Shimano BR-M420, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Shimano Deore BL-M4100, I-spec EV
KASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
TRETLAGER	-
LAUFRÄDER	
FELGEN	Giant AM 29", Tubeless ready, 30mm inner width
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29X2.5" WT 60TPI Foldable, TLR EXO [F] Maxxis Dissector 29X2.40 60TPI Foldable TLR EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	-
GEPÄCKTRÄGER	-

MODELL-MERKMALE

- Rahmen: ALUXX Aaluminum, 120mm FlexPoint suspension system
- Gabel: RockShox Recon Silver RL,130mm travel, Lock-out, Tapered Steerer,15x110mm Boost, MaxleLite, e-MTB optimized
- Schalthebel: Shimano Deore
- Kurbel: Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (Q-factor=168, S:160, M/L:165, XL:170)
- Farbe: Phantom Green

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	406	432	482	507
Sitzrohrwinkel	73.5°	73.5°	73.5°	73.5°
Oberrohrlänge (mm)	580	600	625	650
Steuerrohr-Länge (mm)	100	110	120	135
Steuerrohr-Winkel	67.0°	67.0°	67.0°	67.0°
Gabelneigung (mm)	40	40	40	40
Trail (mm)	113.6	113.6	113.6	113.6
Radstand (mm)	1166	1187	1213	1240
Kettenstreben-Länge (mm)	475	475	475	475
Tretlager-Höhe (mm)	20	20	20	20
Stack (mm)	593	603	612	626
Reach (mm)	404	421	444	465
Überstandshöhe (mm)	741	756	788	792
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	50	50	50	60
Kurbellänge (mm)	160	165	165	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.