

# STANCE E+ 2



## SPEZIFIKATIONEN

| HYBRID CYCLING TECHNOLOGY |                                                                                                    |
|---------------------------|----------------------------------------------------------------------------------------------------|
| MOTOR                     | SyncDrive Sport, 70Nm, powered by Yamaha                                                           |
| SENSOR                    | Giant RideControl One ANT+                                                                         |
| DISPLAY                   | ANT+ Wireless display compatible                                                                   |
| BATTERY                   | EnergyPak Smart 500Wh                                                                              |
| RAHMEN                    |                                                                                                    |
| GRÖSSEN                   | S, M, L, XL                                                                                        |
| FARBE                     | Amber Glow                                                                                         |
| RAHMEN                    | ALUXX Aluminum, 120mm FlexPoint suspension system, 141mm Boost QR, Integrated KS18 Kickstand Mount |
| GABEL                     | SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 thru-axle               |
| DÄMPFER                   | RockShox Monarch R, High Volume, 184x44mm, custom tuned                                            |
| KOMPONENTEN               |                                                                                                    |
| LENKER                    | Giant Connect TR Riser 31.8x780mm                                                                  |
| GRIPS                     | Giant Tactal single lock-on                                                                        |
| VORBAU                    | Giant Contact                                                                                      |
| SATTELSTÜTZE              | Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium                                            |
| SATTEL                    | Giant Sport                                                                                        |
| PEDALE                    | Aluminum Platform                                                                                  |
| ANTRIEB                   |                                                                                                    |
| SCHALTHEBEL               | Shimano Deore, 10-speed                                                                            |
| SCHALTWERK                | Shimano Deore, 10-speed, Shadow+                                                                   |
| BREMSEN                   | Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm                                              |
| BREMSHEBEL                | Tektro HD-M745 Orion                                                                               |
| KASSETTE                  | Shimano CS-M4100-10, 11-46T, 10-speed                                                              |
| KETTE                     | KMC e.10 Sport, e-bike optimized                                                                   |
| KURBEL                    | Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (S:160, M/L:165, XL:170)                |
| TRETLAGER                 | -                                                                                                  |
| LAUFRÄDER                 |                                                                                                    |
| FELGEN                    | Giant AM 29", Tubeless ready, 30mm inner width                                                     |
| NABE                      | Giant eTracker Sport, [F] 15mm Thru-Axle [R] 141mm QR                                              |
| SPEICHEN                  | Stainless Steel                                                                                    |
| REIFEN                    | Maxxis Rekon 29x2.4" foldable, 60tpi, EXO, Tubeless Ready                                          |
| ACCESSORIES               |                                                                                                    |
| LIGHTING                  | -                                                                                                  |
| GEPÄCKTRÄGER              | -                                                                                                  |

## MODELL-MERKMALE

- Rahmen: ALUXX Aluminum, 120mm FlexPoint suspension system, 141mm Boost QR, Integrated KS18 Kickstand Mount
- Gabel: SR Suntour XCR 34 Air LO-R, 130mm travel, tapered steerer, Lockout, 110x15 thru-axle
- Schalthebel: Shimano Deore, 10-speed
- Kurbel: Forged Alloy minimal Q-factor, 36T Steel Direct Mount ring (S:160, M/L:165, XL:170)
- Farbe: Amber Glow

## GEOMETRIEDATEN

| RAHMEN                   | S     | M     | L     | XL    |
|--------------------------|-------|-------|-------|-------|
| Sitzrohlänge (mm)        | 406   | 432   | 482   | 507   |
| Sitzrohrwinkel           | 73.5° | 73.5° | 73.5° | 73.5° |
| Oberrohrlänge (mm)       | 580   | 600   | 625   | 650   |
| Steuerrohr-Länge (mm)    | 100   | 110   | 120   | 135   |
| Steuerrohr-Winkel        | 67.0° | 67.0° | 67.0° | 67.0° |
| Gabelneigung (mm)        | 40    | 40    | 40    | 40    |
| Trail (mm)               | 113.6 | 113.6 | 113.6 | 113.6 |
| Radstand (mm)            | 1166  | 1187  | 1213  | 1240  |
| Kettenstreben-Länge (mm) | 475   | 475   | 475   | 475   |
| Tretlager-Höhe (mm)      | 20    | 20    | 20    | 20    |
| Stack (mm)               | 593   | 603   | 612   | 626   |
| Reach (mm)               | 404   | 421   | 444   | 465   |
| Überstandshöhe (mm)      | 741   | 756   | 788   | 792   |
| Lenkerbreite (mm)        | 780   | 780   | 780   | 780   |
| Vorbaulänge (mm)         | 50    | 50    | 50    | 60    |
| Kurbellänge (mm)         | 160   | 165   | 165   | 170   |
| Radgrösse                | 29"   | 29"   | 29"   | 29"   |

Spezifikations-, Preis- und Farbaenderungen vorbehalten.