



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Raw Carbon / Iris / Reflective Silver
RAHMEN	Advanced SL-Grade Composite, integrated seatpost, disc
GABEL	Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIPS	Stratus Lite 2.0
VORBAU	Giant Contact SLR XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATTELSTÜTZE	Advanced SL-Grade composite, integrated design, -5/+15mm offset
SATTEL	Giant Fleet SLR
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Dura-Ace Di2 ST-R9270
UMWERFER	Shimano Dura-Ace Di2 ST-R9250
SCHALTWERK	Shimano Dura-Ace Di2 ST-R9250
BREMSEN	Shimano Dura-Ace Di2 hydraulic, Shimano RT-MT900 rotors [F]160mm, [R]140mm
BREMSEBEL	Shimano Dura-Ace Di2
KASSETTE	Shimano Dura-Ace, 12-speed, 11x34
KETTE	Shimano Dura-Ace M9100
KURBEL	Shimano Dura-Ace, 36/52 with FC-9200P power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	CADEX 42 Disc WheelSystem
NABE	CADEX 42 Disc WheelSystem, 12mm thru-axle
SPEICHEN	CADEX 42 Disc WheelSystem
REIFEN	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, tubeless prepared, 32mm max tire size

MODELL-MERKMALE

- Rahmen: Advanced SL-Grade Composite, integrated seatpost, disc
- Gabel: Advanced SL-Grade Composite, full-composite OverDrive 2 steerer, disc
- Schalthebel: Shimano Dura-Ace Di2 ST-R9270
- Kurbel: Shimano Dura-Ace, 36/52 with FC-9200P power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farbe: Raw Carbon / Iris / Reflective Silver

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	680	710	740	770	800	830
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	120	130	145	165	185	200
Steuerrohr-Winkel	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Radstand (mm)	976	977	980	991	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Überstandshöhe (mm)	706	725	747	773	800	816
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbauhöhe (mm)	80	90	100	110	110	120
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.