



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Supernova/Carbon
RAHMEN	Advanced-Grade Composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
GABEL	Fox 34 Float SC Factory Live Valve, 110mm, FIT4 damper, Boost 15x110 Kabolt, 44mm offset, custom tuned for Giant
DÄMPFER	Fox Factory Live Valve, 165/45, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SLR XC Flat, composite, 760x35mm
GRIFFE	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
VORBAU	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch dropper, remote S: 125mm travel / 30.9 x 395mm
SATTEL	Fi'zi:k Antares R5 with K:iium rails
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle
BREMSSEN	Shimano Deore XT BR-M8100, hydraulic, Shimano RT-64 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano Deore XT BL-M8100
KASSETTE	SRAM GX, 10x52
KETTE	SRAM GX
KURBEL	SRAM GX, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
TRETLAGER	SRAM DUB, press fit

LAUFRÄDER	
FELGEN	Giant XCR 1 30 Carbon WheelSystem, 30mm inner width
NABE	[F] Giant XC alloy, CenterLock, [R] Giant XC alloy, DT350 internal, 54t ratchet system, CenterLock
SPEICHEN	Sapim Laser
REIFEN	Maxxis Recon Race 29x2.4, foldable, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	390	420	465	495
Sitzrohrwinkel	75.5°	75.5°	75.5°	75.5°
Oberrohrlänge (mm)	572	604	626	653
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Radstand (mm)	1127	1159	1183	1212
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	42	42	42	42
Stack (mm)	489	593	603	612
Reach (mm)	420	450	470	495
Überstandshöhe (mm)	745	750	777	800
Lenkerbreite (mm)	760	760	760	760
Vorbaulänge (mm)	60	70	70	70
Kurbellänge (mm)	170	175	175	175
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.