

EXPLORE E+ PRO 1 GTS (DD)



Spezifikationen

Hybrid Cycling Technology	
MOTOR	Giant SyncDrive Pro 2 85Nm, powered by Yamaha, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo 2 remote, Smart Assist automatic mode, 5 support levels, USB-C (10W)
DISPLAY	Giant RideDash EVO, high-angle visibility, 3" full color LCD display, on-board navigation
BATTERY	Giant EnergyPak 800Wh, 22700 Lithium cell technology, Aluminium casing with highest safety standard (EN50604)
CHARGER	Giant EnergyPak 6A smart charger, 60% charge in 3:00h
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
Rahmen	
Größen	M, L, XL, XXL
Farbe	Truffle
Rahmen	ALUXX aluminum, Overdrive 1.8" - 1.5" head tube, integrated battery, integrated KSA40 kickstand mount
Gabel	SR Suntour XCR34 Air Boost, 100mm travel, Hydraulic Lockout, 15x110mm AH Axle
Komponenten	
Lenker	Giant Contour Comfort Riser 31.8x690mm
Griffe	Giant Connect Ergo Max Cork w/bar-end
Vorbau	Giant Contour EVO integrated 16° (S/M:80mm L/XL/XXL 100mm)
Sattelstütze	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
Sattel	Selle Royal Vivo Ergo Moderate Unisex
Pedale	Aluminum Platform
Antrieb	
Schalthebel	Shimano Deore, LinkGlide
Schaltwerk	Shimano Deore LinkGlide, 10-speed, Shadow+
Bremsen	Shimano BR-MT410, hydraulic disc, 180mm
Bremshebel	Shimano Deore
Kassette	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
Kette	Shimano LinkGlide, CN-LG500
Kurbel	Forged Alloy Direct spider/chainguard 46T Steel narrow/wide chainring

Laufräder	
Felgen	eX25, Tubeless Ready, 622x25 Aluminium
Nabe	Giant eTracker, [F] 110x15 [R] 148x12
Speichen	Stainless steel, e-bike optimized
Reifen	Crosscut Gravel 1, 700x57c, Foldable, Tubeless Ready
Extras	KSA40 direct mount kickstand
Accessories	
Lighting	Recon E HL100 StVZO [F] AXA NYX 6-12V E-bike tail light with brake sensor [R]
Lock	
Gepäckträger	MIK HD rack. System bag & basket compatible
Fender/Chainguard	Alluminum Fenders

Geometriedaten

Rahmen	M	L	XL	XXL
Sitzrohlrlänge (mm)	435	485	535	585
Sitzrohrwinkel	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	600	610	630	650
Steuerrohr-Länge (mm)	140	155	170	185
Steuerrohr-Winkel	69.5°	69.5°	69.5°	69.5°
Gabelneigung (mm)	51	51	51	51
Trail (mm)	84.3	84.3	84.3	84.3
Radstand (mm)	1144	1155	1176	1197
Kettenstreben-Länge (mm)	470	470	470	470
Tretlager-Höhe (mm)	60	60	60	60
Stack (mm)	668	682	696	710
Reach (mm)	396	401	417	433
Lenkerbreite (mm)	690	690	690	690
Vorbaulänge (mm)	80	100	100	100
Kurbellänge (mm)	170	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.