

REVOLT ADVANCED 0



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Charcoal Plum, Helios Orange
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-810, 2x11
UMWERFER	Shimano GRX RX-810
SCHALTWERK	Shimano GRX RX-810
BREMSEN	Shimano GRX RX-810 hydraulic, Shimano SM-RT70 rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-810 hydraulic
KASSETTE	Shimano CS-HG800, 11-speed, 11x34
KETTE	KMC X11SL-1
KURBEL	Shimano GRX RX-810, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant CXR 2 Carbon Disc WheelSystem, [F] 35mm, [R] 35mm
NABE	[F] Giant alloy, CenterLock, 12mm thru-axle, [R] Giant alloy, 3-pawl driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim Sprint
REIFEN	CADEX AR, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout
- Gabel: Advanced-Grade Composite, full-composite OverDrive steerer, 12mm thru-axle, disc
- Schalthebel: Shimano GRX RX-810, 2x11
- Kurbel: Shimano GRX RX-810, 31/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farbe: Charcoal Plum, Helios Orange

GEOMETRIEDATEN

RAHMEN	XS		S		M		ML		L		XL
	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	SHORT	LONG	
Sitzrohlänge (mm)	430	450	450	470	470	490	490	510	510	530	550
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.5°	73.5°	73.0°	73.0°	73.0°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	550	560	560	575	575	585	585	600	610
Steuerrohr-Länge (mm)	125	135	135	150	150	165	165	180	180	190	200
Steuerrohr-Winkel	70.0°	71.0°	71.0°	71.5°	71.5°	72.0°	72.0°	72.0°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50	50	50	50	50	50
Trail (mm)	78 82	72 75	72 75	68 72	68 72	65 68	65 68	65 68	65 68	65 68	65 68
Radstand (mm)	1029 1039	1025 1035	1025 1035	1030 1040	1030 1040	1035 1045	1035 1045	1045 1055	1045 1055	1050 1060	1060 1070
Kettenstreben-Länge (mm)	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440	430 440
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81	80 81
Stack (mm)	556	570	570	586	586	602	602	616	616	632	646
Reach (mm)	381	381	381	387	387	391	391	397	397	403	409
Überstandshöhe (mm)	717 724	734 741	734 741	752 759	752 759	769 776	769 776	786 793	786 793	803 810	810 817
Lenkerbreite (mm)	420	420	420	440	440	440	440	460	460	460	460
Vorbaulänge (mm)	50	60	60	70	70	80	80	80	80	90	90
Kurbellänge (mm)	170	170	170	172.5	172.5	172.5	172.5	175	175	175	175
Radgrösse	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C	700x 42C 50C

Spezifikations-, Preis- und Farbänderungen vorbehalten.