



SPEZIFIKATIONEN

| RAHMEN | |
|--------------|--|
| GRÖSSEN | XS, S, M, M/L, L, XL |
| FARBE | Gloss Misty Forest/Matte Black Diamond |
| RAHMEN | Advanced-Grade Composite, 12x142mm thru-axle, disc, flip chip dropout |
| GABEL | RockShox Rudy XPLR, 40mm, cartridge damper 12x100mm thru-axle |
| DÄMPFER | N/A |
| KOMPONENTEN | |
| LENKER | Giant Contact SL XR D-Fuse, 16-degree flare XS:44cm, S:44cm, M:46cm, M/L:46cm, L:48cm, XL:48cm |
| GRIFFE | Stratus Lite 3.0 |
| VORBAU | Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL: 80mm |
| SATTELSTÜTZE | Postmodern, dropper, 30.9mm with 25mm of suspension XS:365mm / 75mm drop S:415mm / 100mm drop M:415mm / 100mm drop M/L: 415mm / 100mm drop L:415mm / 100mm drop XL: 415mm / 100mm drop |
| SATTEL | Giant Approach SL |
| PEDALE | N/A |
| ANTRIEB | |
| SCHALTHEBEL | SRAM Rival 1, 1x11 |
| UMWERFER | N/A |
| SCHALTWERK | SRAM Rival 1 |
| BREMSSEN | SRAM Rival 1 hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm |
| BREMSHEBEL | SRAM Rival 1, left lever dropper switch |
| KASSETTE | SRAM Rival, 11-speed, 11x42 |
| KETTE | SRAM PC-1130 |
| KURBEL | SRAM Rival D1 DUB, 40t XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| TRETLAGER | SRAM DUB, press fit |

| LAUFRÄDER | |
|-----------|---|
| FELGEN | Giant CXR X1 Carbon Disc WheelSystem, [F] 25.8mm, [R] 25.8mm |
| NABE | [F] Giant AR alloy, CenterLock, 12mm thru-axle [R] Giant AR alloy, DT350 36t ratchet system, CenterLock, 12mm thru-axle |
| SPEICHEN | Sapim CX-Ray |
| REIFEN | Giant CrossCut Grip 1, 700x45c, tubeless |
| EXTRAS | tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position |

GEOMETRIEDATEN

| RAHMEN | XS | | S | | M | | ML | | L | | XL |
|--------------------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|---------------|
| | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG | SHORT | LONG | SH |
| Sitzrohrlänge (mm) | 430 | 450 | 450 | 470 | 470 | 490 | 490 | 510 | 510 | 530 | 530 |
| Sitzrohrwinkel | 74.0° 73.9° | 73.5° 73.4° | 73.5° 73.4° | 73.5° 73.4° | 73.0° 72.9° | 73.0° 72.9° | 73.0° 72.9° | 73.0° 72.9° | 73.0° 72.9° | 73.0° 72.9° | 73.0° 72.9° |
| Oberrohrlänge (mm) | 543 | 553 | 560 | 575 | 585 | 600 | 600 | 615 | 615 | 630 | 630 |
| Steuerrohr-Länge (mm) | 90 | 100 | 115 | 130 | 145 | 160 | 160 | 175 | 175 | 190 | 190 |
| Steuerrohr-Winkel | 70.5° 70.4° | 71.0° 70.9° | 71.5° 71.4° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° | 72.0° 71.9° |
| Gabelneigung (mm) | 45 | 45 | 45 | 45 | 45 | 45 | 45 | 45 | 45 | 45 | 45 |
| Trail (mm) | 80.3 83.7 | 76.9 80.3 | 73.5 76.8 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 | 70.1 73.4 |
| Radstand (mm) | 1023 1033 | 1024 1034 | 1026 1036 | 1031 1041 | 1041 1051 | 1051 1061 | 1051 1061 | 1051 1061 | 1051 1061 | 1051 1061 | 1051 1061 |
| Kettenstreben-Länge (mm) | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 | 425 435 |
| Tretlager-Höhe (mm) | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 | 68 69 |
| Stack (mm) | 549 | 560 | 576 | 592 | 607 | 622 | 622 | 637 | 637 | 652 | 652 |
| Reach (mm) | 386 | 387 | 389 | 393 | 399 | 410 | 410 | 415 | 415 | 420 | 420 |
| Überstandshöhe (mm) | 720 726 | 736 743 | 755 761 | 772 778 | 790 796 | 808 814 | 808 814 | 814 820 | 814 820 | 820 826 | 820 826 |
| Lenkerbreite (mm) | 440 | 440 | 460 | 460 | 480 | 480 | 480 | 480 | 480 | 480 | 480 |
| Vorbaulänge (mm) | 50 | 60 | 70 | 80 | 80 | 80 | 80 | 80 | 80 | 80 | 80 |
| Kurbellänge (mm) | 170 | 170 | 172.5 | 172.5 | 175 | 175 | 175 | 175 | 175 | 175 | 175 |
| Radgrösse | 700c | 700c | 700c | 700c | 700c | 700c | 700c | 700c | 700c | 700c | 700c |

Spezifikations-, Preis- und Farbänderungen vorbehalten.