

# STANCE E+ 1 PRO

**GIANT**

## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
BATTERY	EnergyPak Smart 800, EnergyPak Plus 250Wh range extender compatible
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Cordovan
RAHMEN	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
GABEL	RockShox 35 Silver, 140mm, 1.8" tapered steerer, 110x15 Maxle Stealth
DÄMPFER	SR Suntour Raidon R, 190x45mm, custom tuned
KOMPONENTEN	
LENKER	Giant Connect TR Riser 31.8x780mm
GRIFFE	Giant Tactal single lock-on
VORBAU	Giant Contact
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SATTEL	Giant Sport
PEDALE	Flat pedal
ANTRIEB	
SCHALTHEBEL	Shimano Deore
SCHALTWERK	Shimano Deore 12-speed
BREMSEN	Tektro HD-M750 Orion, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Tektro HD-M750
KASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	Giant AM 29", Tubeless ready, 30mm inner width
NABE	Shimano MT410 Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29X2.50" Foldable, TLR, EXO, 60TPI [F]Maxxis Dissector 29X2.40" Foldable, WT, TLR, EXO, 60TPI [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)
ACCESSORIES	
LIGHTING	-
LOCK	Torx 25 Battery Lock with built-in Torque limiter
GEPÄCKTRÄGER	-

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	400	425	450	475
Sitzrohrwinkel	76.0°	76.0°	76.0°	76.0°
Oberrohrlänge (mm)	580	607	639	671
Steuerrohr-Länge (mm)	105	115	125	135
Steuerrohr-Winkel	65.5°	65.5°	65.5°	65.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Radstand (mm)	1204	1233	1267	1301
Kettenstreben-Länge (mm)	468	468	468	468
Tretlager-Höhe (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Überstandshöhe (mm)	760	760	780	796
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	165	165	165
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.