



## SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Sport, 75Nm, powered by Yamaha
SENSOR	RideControl Dash
DISPLAY	RideControl Dash, full color lcd screen
BATTERY	EnergyPak Smart 625, EnergyPak Plus 250Wh range extender compatible
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Charcoal Plum
RAHMEN	ALUXX SL-grade aluminum, 125mm travel FlexPoint suspension system, 148x12 rear axle, Universal Derrailleur hanger, 184x44 shock, 1.5~1.8" headset
GABEL	SR Suntour XCR 34 LO-R, 140mm travel, tapered steerer, Lockout, 110x15 thru-axle
DÄMPFER	SR Suntour Raidon R, 190x45mm, custom tuned
KOMponenten	
LENKER	Giant Connect TR Riser 31.8x780mm
GRIFFE	Giant Connect ErgoMax lock-on
VORBAU	Giant Contact
SATTELSTÜTZE	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SATTEL	Giant Sport
PEDALE	Aluminum Platform
ANTRIEB	
SCHALTHEBEL	Shimano Deore LinkGlide
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano Deore LinkGlide, 10-speed
BREMSEN	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Tektro HD-M745 Orion
KASSETTE	Shimano LinkGlide, CS-LG400-10, 11-43T, 10-speed
KETTE	Shimano, LinkGlide, CN-LG500
KURBEL	FSA Comet E-Bike crank arm setFSA MegaTooth Direct-mount 1X steel 36T
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	Giant AM, Tubeless ready, 30mm inner width [F] 27.5" (S size), 29" (M/L/XL size) [R] Giant AM 27.5", Tubeless ready, 30mm inner width
NABE	Giant eTracker Boost, [F] 110x15 [R] 148x12mm
SPEICHEN	Stainless Steel
REIFEN	Maxxis Rekon 27.5x2.4"(S size), 29x2.4" (M/L/XL size), Foldable, TLR, EXO, 60TPI [F], Maxxis Rekon 27.5x2.4" Foldable, TLR, EXO, 60TPI [R]
EXTRAS	-
ACCESSORIES	
LIGHTING	Giant Rekon E50 HLAXa BlueLine Steady E6 rear
LOCK	Torx 25 Battery Lock with built-in Torque limiter
GEPÄCKTRÄGER	Giant Rack-It MIK

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	400	425	450	475
Sitzrohrwinkel	76.0°	76.0°	76.0°	76.0°
Oberrohrlänge (mm)	580	607	639	671
Steuerrohr-Länge (mm)	105	115	125	135
Steuerrohr-Winkel	65.5°	65.5°	65.5°	65.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	124	124	124	124
Radstand (mm)	1204	1233	1267	1301
Kettenstreben-Länge (mm)	468	468	468	468
Tretlager-Höhe (mm)	40	40	40	40
Stack (mm)	618	627	636	646
Reach (mm)	425	450	480	510
Überstandshöhe (mm)	760	760	780	796
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	165	165	165
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.