

# TCR ADVANCED DISC 1 KOM

**GIANT**



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Cold Night, Unicorn White
RAHMEN	Advanced-Grade Composite, disc
GABEL	Advanced-Grade Composite, full-composite OverDrive steerer, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIFFE	Stratus Lite 2.0
VORBAU	Giant Contact XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATTELSTÜTZE	Giant Variant, composite, -5/+15mm offset
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano 105 Di2
UMWERFER	Shimano 105 Di2
SCHALTWERK	Shimano 105 Di2
BREMSEN	Shimano 105 Di2 hydraulic, Giant MPH rotors [F]160mm, [R]140mm
BREMSHEBEL	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x34
KETTE	KMC X12
KURBEL	Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant P-R2 Disc wheelset, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	Giant Course 1, tubeless, 700x25c (28mm), folding
EXTRAS	tubeless prepared, 32mm max tire size

## MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, disc
- Gabel: Advanced-Grade Composite, full-composite OverDrive steerer, disc
- Schalthebel: Shimano 105 Di2
- Kurbel: Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
- Farbe: Cold Night, Unicorn White

## GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohlänge (mm)	425	445	470	500	530	560
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	120	130	145	165	185	200
Steuerrohr-Winkel	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Radstand (mm)	976	977	980	991	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Überstandshöhe (mm)	706	725	747	773	800	816
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbauhöhe (mm)	80	90	100	110	110	120
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.