



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Cold Night/Chrome
RAHMEN	Advanced-Grade Composite, disc
GABEL	Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SLR XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIFFE	Stratus Lite 2.0
VORBAU	Giant Contact SL XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm
SATTELSTÜTZE	Giant Variant, composite, -5/+15mm offset
SATTEL	Giant Fleet SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano Ultegra Di2 ST-R8170
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSEN	Shimano Ultegra Di2 hydraulic, Shimano RT-MT800 rotors [F]160mm, [R]140mm
BREMSHEBEL	Shimano Ultegra Di2 hydraulic
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano Ultegra
KURBEL	Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
TRETLAGER	Shimano, press fit
LAUFRÄDER	
FELGEN	Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim CX-Ray
REIFEN	CADEX Race, tubeless, 700x25c (26.5mm), folding
EXTRAS	computer mount, tubeless prepared, 32mm max tire size

## MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite, disc
- Gabel: Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc
- Schalthebel: Shimano Ultegra Di2 ST-R8170
- Kurbel: Shimano Ultegra, 36/52 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175m
- Farbe: Cold Night/Chrome

## GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	425	445	470	500	530	560
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	72.5°
Oberrohrlänge (mm)	520	535	550	565	580	600
Steuerrohr-Länge (mm)	120	130	145	165	185	200
Steuerrohr-Winkel	71.0°	72.3°	73.0°	73.0°	73.0°	73.0°
Gabelneigung (mm)	45	45	45	45	45	45
Trail (mm)	72.1	64	59.2	59.2	59.2	59.2
Radstand (mm)	976	977	980	991	1006	1020
Kettenstreben-Länge (mm)	405	405	405	405	405	405
Tretlager-Höhe (mm)	72	70	70	67	67	67
Stack (mm)	517	528	545	562	581	596
Reach (mm)	376	383	388	393	402	412
Überstandshöhe (mm)	706	725	747	773	800	816
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbauhöhe (mm)	80	90	100	110	110	120
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.