

TRANCE X ADVANCED E+ ELITE 2



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	SyncDrive Pro, 85Nm, powered by Yamaha
SENSOR	RideControl GO integrated in TT, RideControl Ergo 3
DISPLAY	ANT+ cycle computer compatible
AKKU	EnergyPak Smart 400, EnergyPak Plus range extender compatible
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Amber Glow/Cordovan
RAHMEN	Advanced-grade composite frame, Advanced-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
GABEL	Fox 36 Float Performance, 150mm travel, 44mm offset, Grip 3-position Micro Adjust damper, Boost 110x15QR
DÄMPFER	Fox DPS Performance, EVOL Large Volume sleeve, 3-position Lever, 185x52.5mm Trunnion mount, custom tuned
KOMponenten	
LENKER	Giant Contact SL 35 Trail, 35x780mm
GRIFFE	Giant Tactal Pro-E, single lock-on
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm (S:125/M:150/ L&XL:170)
SATTEL	Giant Romero, Neutral
PEDALE	n/a
ANTRIEB	
SCHALTHEBEL	Shimano Deore SLX
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano Deore SLX, 12-speed, Shadow+
BREMSEN	Shimano SLX BR-M7120, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Shimano SLX, I-spec EV
KASSETTE	Shimano HG-M6100, 10-51T, 12-speed
KETTE	KMC e.12 Sport, NP/NP, e-bike optimized
KURBEL	Praxis Wavetm 36T Cold Forged 4130 premium steel Praxis e-Cadet+ custom forged crankarm set (S:160, M/L: 165, XL:170)
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	Giant AM 29" [F]/ 27.5" [R], Tubeless ready, 30mm inner width, e-bike optimized
NABE	Shimano MT410, Boost, Center-Lock, [F] 110x15 [R] 148x12mm Micro-Spline Drive Body Thru-axle
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F] Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool) Inner tube supplied
ACCESSORIES	
BELEUCHTUNG	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	400	425	450	475
Sitzrohrwinkel	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°
Oberrohrlänge (mm)	577 575	607 605	636 634	665 663
Steuerrohr-Länge (mm)	95	100	115	130
Steuerrohr-Winkel	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	113.1 108	113.1 108	113.1 108	113.1 108
Radstand (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Kettenstreben-Länge (mm)	447 447	447 447	447 447	447 447
Tretlager-Höhe (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Überstandshöhe (mm)	726 735	733 742	732 741	741 750
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	160	165	165	170
Radgrösse	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"	R27.5" / F29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.