

TRANCE X ADVANCED PRO 29 1



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Messier/Black/Chrome
RAHMEN	Advanced-Grade Composite front and rear triangles, 135mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle
GABEL	Fox 36 Factory Live Valve, FIT4 damper, 44mm offset, 150mm, 15x110 Kabolt X, custom tuned for Giant
DÄMPFER	Fox Factory Live, 185/55, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact SLR TR35, composite, 780x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single S:120mm, M:120mm, L:130mm, XL:130mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATTELSTÜTZE	TranzX travel-adjustable dropper, remote S: 120-150mm travel / 30.9 x 459mm M: 140-170mm travel / 30.9 x 499mm
SATTEL	Giant Romero SL
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle
BREMSEN	SRAM G2 RSC, hydraulic, SRAM CenterLine rotors [F]200mm, [R]180mm
BREMSHEBEL	SRAM G2 RSC
KASSETTE	SRAM GX-1275, 10x52
KETTE	SRAM GX Eagle
KURBEL	SRAM GX, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM DUB, press fit
LAUFRÄDER	
FELGEN	Giant TRX 2 29 Carbon WheelSystem, 30mm inner width
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPEICHEN	Sapim
REIFEN	[F] Maxxis Minion DHF 29x2.5 WT, 3C MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4, EXO, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front and rear triangles, 135mm Maestro suspension, flip chip - Maestro, 12x148mm thru-axle
- Gabel: Fox 36 Factory Live Valve, FIT4 damper, 44mm offset, 150mm, 15x110 Kabolt X, custom tuned for Giant
- Schalthebel: SRAM GX Eagle, 1x12
- Kurbel: SRAM GX, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
- Farbe: Messier/Black/Chrome

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohlänge (mm)	430	430	465	496
Sitzrohrwinkel	77.2° 77.9°	77.2° 77.9°	77.2° 77.9°	77.2° 77.9°
Oberrohrlänge (mm)	566 564	597 595	629 627	656 654
Steuerrohr-Länge (mm)	95	100	110	120
Steuerrohr-Winkel	65.5° 66.2°	65.5° 66.2°	65.5° 66.2°	65.5° 66.2°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	125.1 119.5	125.1 119.5	125.1 119.7	125.1 119.5
Radstand (mm)	1173 1172	1205 1204	1239 1238	1268 1266
Kettenstreben-Länge (mm)	438 435	438 435	438 435	438 435
Tretlager-Höhe (mm)	40 30	40 30	40 30	40 30
Stack (mm)	617 611	621 615	631 624	640 634
Reach (mm)	426 434	456 464	486 494	511 519
Überstandshöhe (mm)	735 743	729 738	754 763	777 786
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.