

TRANCE X ADVANCED E+ ELITE 3



SPEZIFIKATIONEN

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro2 85Nm, PedalPlus 6-Sensor technology
SENSOR	Giant RideControl Ergo3, grip integrated remote
DISPLAY	Giant RideControl GO, frame integrated LED console Optional wireless ANT+ display
AKKU	Giant EnergyPak 400Wh, Aluminium casing with highest safety standard (EN50604), CO2 Neutral production, Giant EnergyPak Plus 200 range extender compatible
CHARGER	Giant EnergyPak 4A smart charger, 60% in 1:45
CONNECTIVITY	Giant RideControl App enabled ANT+ wireless display signal with e-bike profile
RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Messier/Panther
RAHMEN	Advanced-grade composite frame, AluXX SL-grade rear triangle, Advanced forged composite upper rocker, 140mm Maestro suspension system
GABEL	Marzocchi Bomber Z2 E-Tuned, 29er, 150mm travel, 44mm offset, RAIL damper Sweep-Adj, Kabolt 110
DÄMPFER	Fox Float Performance, EVOL Large Volume sleeve, 2pos, 185x52.5mm Trunnion mount, custom tuned, recommended sag: 30%
KOMPONENTEN	
LENKER	Giant Contact SL 35 Trail, 35x780mm
GRIFFE	Giant Tactal Pro-E, tapered design, 135mm Ø28-30mm (S/M) 142mm Ø29-32mm (L/XL)
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Tranz-X Rad+ dropper, 30,9mm, 30mm travel adjustable (S:120-150mm, M:140-170mm, L/XL:170-200mm)
SATTEL	Giant Romero, Neutral
PEDALE	n/a
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	MRP HD2 co-moulded chain guide
SCHALTWERK	Shimano Deore 12-speed, Shadow+
BREMSEN	Shimano BR-MT420, 4-piston, hydraulic disc, 203mm [F/R]
BREMSHEBEL	Shimano Deore, I-spec EV
KASSETTE	Shimano CS-M6100-12, 10-51T, 12-speed
KETTE	KMC e.12 Turbo, EcoProteq, e-bike optimized
KURBEL	Praxis N.W. 36T Cold Forged 4130 premium steel Praxis e-Cranks (Q-factor=168, S:160, M/L:165, XL:170)
TRETLAGER	n/a

LAUFRÄDER	
FELGEN	Giant AM30, Tubeless ready, 30mm inner width, 29" [F] / 27.5" [R]
NABE	Shimano MT410 Boost, Center-Lock, 110x15 [F] 148x12 Shimano Micro-Spline Drive Body Thru-axle [R]
SPEICHEN	Sapim E-Lite [R] Race [F], e-bike optimized
REIFEN	Maxxis Minion DHF 29x2.50" Foldable, TLR, EXO [F]Maxxis Dissector 27.5x2.4" Foldable, TLR, EXO [R]
EXTRAS	Tubeless kit (liquid, valves, levers, manual, tool)Inner tube supplied
ACCESSORIES	
BELEUCHTUNG	Optional:- Giant Recon series e-bike lights available and direct connectable

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
	LOW HIGH	LOW HIGH	LOW HIGH	LOW HIGH
Sitzrohrlänge (mm)	400	425	450	475
Sitzrohrwinkel	77.2° 78.0°	76.0° 76.7°	76.0° 76.7°	76.0° 76.7°
Oberrohrlänge (mm)	577 575	607 605	636 634	665 663
Steuerrohr-Länge (mm)	95	100	115	130
Steuerrohr-Winkel	65.7° 66.5°	65.8° 66.5°	65.8° 66.5°	65.8° 66.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	113.1 108	113.1 108	113.1 108	113.1 108
Radstand (mm)	1194 1195	1215 1212	1244 1244	1275 1275
Kettenstreben-Länge (mm)	447 447	447 447	447 447	447 447
Tretlager-Höhe (mm)	10	10	10	10
Stack (mm)	607 601	611 605	625 619	639 633
Reach (mm)	439 447	457 462	480 487	505 513
Überstandshöhe (mm)	726 735	733 742	732 741	741 750
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	160	165	165	170
Radgrösse	R27.5" / F	R27.5" / F	R27.5" / F	R27.5" / F

Spezifikations-, Preis- und Farbänderungen vorbehalten.