

# TCR ADVANCED PRO DISC 1 AR

**GIANT**

## SPEZIFIKATIONEN

| RAHMEN       |  |
|--------------|--|
| GRÖSSEN      | XS, S, M, M/L, L, XL   |
| FARBE        | Charcoal Plum  |
| RAHMEN       | Advanced-Grade Composite, disc   |
| GABEL        | Advanced-Grade Composite, full-composite OverDrive 2 steerer, disc   |
| DÄMPFER      | N/A  |
| KOMPONENTEN  |  |
| LENKER       | Giant Contact SL XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm  |
| GRIFFE       | Stratus Lite 2.0   |
| VORBAU       | Giant Contact SL XS:80mm, S:90mm, M:100mm, M/L:110mm, L:110mm, XL:120mm  |
| SATTELSTÜTZE | Giant Variant, composite, -5/+15mm offset  |
| SATTEL       | Giant Fleet SL   |
| PEDALE       | N/A  |
| ANTRIEB      |  |
| SCHALTHEBEL  | SRAM Rival eTap AXS  |
| UMWERFER     | SRAM Rival eTap AXS  |
| SCHALTWERK   | SRAM Rival eTap AXS  |
| BREMSEN      | SRAM Rival eTap AXS hydraulic, SRAM PaceLine rotors [F]160mm, [R]160mm   |
| BREMSHEBEL   | SRAM Rival eTap AXS hydraulic  |
| KASSETTE     | SRAM Rival, 12-speed, 10x36  |
| KETTE        | SRAM Rival D1  |
| KURBEL       | SRAM Rival D1 DUB, 33/46with Power Halo power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm |
| TRETLAGER    | SRAM DUB, press fit  |

| LAUFRÄDER |  |
|-----------|--|
| FELGEN    | Giant SLR 1 36 Carbon Disc WheelSystem, [F] 36mm, [R] 36mm   |
| NABE      | [F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle |
| SPEICHEN  | Sapim CX-Ray   |
| REIFEN    | Giant Gavia Fondo 1, tubeless, 700x28c (32mm), folding   |
| EXTRAS    | computer mount, tubeless prepared, 32mm max tire size  |

## GEOMETRIEDATEN

| RAHMEN                   | XS    | S     | M     | ML    | L     | XL    |
|--------------------------|-------|-------|-------|-------|-------|-------|
| Sitzrohrlänge (mm)       | 425   | 445   | 470   | 500   | 530   | 560   |
| Sitzrohrwinkel           | 74.5° | 74.0° | 73.5° | 73.0° | 73.0° | 72.5° |
| Oberrohrlänge (mm)       | 520   | 535   | 550   | 565   | 580   | 600   |
| Steuerrohr-Länge (mm)    | 120   | 130   | 145   | 165   | 185   | 200   |
| Steuerrohr-Winkel        | 71.0° | 72.3° | 73.0° | 73.0° | 73.0° | 73.0° |
| Gabelneigung (mm)        | 45    | 45    | 45    | 45    | 45    | 45    |
| Trail (mm)               | 72.1  | 64    | 59.2  | 59.2  | 59.2  | 59.2  |
| Radstand (mm)            | 976   | 977   | 980   | 991   | 1006  | 1020  |
| Kettenstreben-Länge (mm) | 405   | 405   | 405   | 405   | 405   | 405   |
| Tretlager-Höhe (mm)      | 72    | 70    | 70    | 67    | 67    | 67    |
| Stack (mm)               | 517   | 528   | 545   | 562   | 581   | 596   |
| Reach (mm)               | 376   | 383   | 388   | 393   | 402   | 412   |
| Überstandshöhe (mm)      | 706   | 725   | 747   | 773   | 800   | 816   |
| Lenkerbreite (mm)        | 400   | 400   | 420   | 420   | 440   | 440   |
| Vorbaulänge (mm)         | 80    | 90    | 100   | 110   | 110   | 120   |
| Kurbellänge (mm)         | 170   | 170   | 172.5 | 172.5 | 175   | 175   |
| Radgrösse                | 700C  | 700C  | 700C  | 700C  | 700C  | 700C  |

Spezifikations-, Preis- und Farbänderungen vorbehalten.