



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Charcoal/Milky Way, Black/Helios Orange
RAHMEN	Advanced-grade composite, disc
GABEL	Advanced-grade composite, full-composite steerer, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SL D-Fuse XS:40cm, S:40cm, M:42cm, M/L:42cm, L:44cm, XL:44cm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse, composite, 14mm offset
SATTEL	Giant Approach
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	Shimano 105 Di2
UMWERFER	Shimano 105 Di2
SCHALTWERK	Shimano 105 Di2
BREMSEN	Shimano 105 Di2 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano 105 Di2
KASSETTE	Shimano 105, 12-speed, 11x36
KETTE	KMC X12L-1
KURBEL	Shimano 105, 34/50 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant P-R2 Disc wheelset, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	Sapim stainless
REIFEN	Giant Gavia Fondo 1, tubeless, 700x32c (33.5mm), folding
EXTRAS	Tubeless Bereifung, maximale Reifenbreite 38 mm, Bidonhalter Schutzblech-Aufnahme

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	410	445	480	515	535	565
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	530	545	560	575	595
Steuerrohr-Länge (mm)	120	140	150	175	195	215
Steuerrohr-Winkel	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Radstand (mm)	995	994	998	1010	1025	1040
Kettenstreben-Länge (mm)	420	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Überstandshöhe (mm)	705	733	762	796	814	841
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.