



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S/M, M/L, L/XL
FARBE	Shoreline/Carbon
RAHMEN	Advanced-grade composite front and rear triangles, 200mm Maestro suspension, flip chip - headset, flip chip - dropout DH, flip chip - Maestro 3, 12x157mm thru-axle, 27.5 or 29-inch rear wheel compatible
GABEL	Fox 40 Factory, GRIP2 damper, 203mm, 20x110, custom tuned for Giant
DÄMPFER	Fox DHX2 Factory, SLS coil, 225/75, custom tuned for Giant S/M #425, M/L #450, L/XL #475
KOMPONENTEN	
LENKER	Giant Contact SL TR35, composite, 800x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single
VORBAU	TruVativ Descendant Direct Mount, 35 S/M:50mm, M/L:50mm, L/XL:50mm
SATTELSTÜTZE	Giant Contact, 30.9mm, 0 offset, 400mm
SATTEL	Giant Romero
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle DH, 1x7
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle DH
BREMSEN	Shimano Saint M-820, hydraulic, Shimano RT-66 rotors, [F]220mm, [R]203mm
BREMSHEBEL	Shimano Saint BL-M820
KASSETTE	SRAM GX DH, 11-25
KETTE	SRAM PC 1110
KURBEL	TruVativ Descendant DH, 34t, 56.5mm chainline, S/M:165mm, M/L:170mm, L/XL:170mm
TRETLAGER	SRAM DUB, threaded, 83mm

LAUFRÄDER	
FELGEN	Giant AM30, alloy, 28-hole, 30mm inner width
NABE	[F] alloy, sealed cartridge, 6-bolt, 20x110mm [R] alloy, 72t pawl driver, sealed cartridge, 6-bolt, 12x157mm
SPEICHEN	Sapim Laser, straight pull, DBL
REIFEN	[F] Maxxis Assegai 29x2.5 WT, 3C MaxxGrip, DH, TR [R] Maxxis Minion DHR II 27.5x2.4 WT, 3C, MaxxGrip, DH, TR tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 36t max chainring size, MRP SXg chain guide, full downtube protector. *Not compatible with 2023 or earlier RockShox BoXXer Ultimate or BoXXer Select

GEOMETRIEDATEN

RAHMEN	S/M			M/L			L/XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	430			450			450		
SeatpostInsertionDepth (mm)	155			165			165		
Sitzrohrwinkel	78.4°	78.7°	79.1°	78.4°	78.8°	79.1°	78.5°	78.8°	79.1°
Oberrohrlänge (mm)	571.2	570.5	569.8	591.3	590.5	589.8	611.3	610.6	609.8
Steuerrohr-Länge (mm)	110			110			110		
Steuerrohr-Winkel	61.6°	61.9°	62.3°	61.6°	62.0°	62.3°	61.7°	62.0°	62.3°
Gabelneigung (mm)	52			52			52		
Trail (mm)	146.4	143.6	140.8	146.2	143.5	140.8	146	143.3	140.8
Radstand (mm)	1273	1271.9	1270.6	1293	1291.8	1290.6	1313	1311.9	1310.6
Kettenstreben-Länge (mm)	447.9	446.5	445	447.9	446.5	445	447.9	446.5	445
Tretlager-Höhe (mm)	13.1	8.1	3	13.3	8.3	3.1	13.5	8.4	3.2
Stack (mm)	634.6	631.9	629.1	634.9	632.2	629.2	635.3	632.4	629.3
Reach (mm)	440.9	444.7	448.6	461.2	464.9	468.6	481.5	485.1	488.6
Überstandshöhe (mm)	733.7	738.2	742.9	735.2	740	744.8	742.9	747.6	752.3
Lenkerbreite (mm)	800			800			800		
Vorbaulänge (mm)	50			50			50		
Kurbellänge (mm)	165			165			165		
Radgrösse	R27.5" / F29"			R27.5" / F29"			R27.5" / F29"		

Spezifikations-, Preis- und Farbänderungen vorbehalten.