



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Metallic Black
RAHMEN	ALUXX-grade aluminum, 125mm FlexPoint suspension, 12x148mm thru-axle
GABEL	Crest 34 SL RCL, 140mm, Boost 15x110 QR, custom tuned for Giant
DÄMPFER	Suntour Raidon R, 190x45
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 780x35mm
GRIFFE	Giant Sole-O
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATTELSTÜTZE	Giant Contact Switch AT dropper, remote S: 140mm - 110mm travel / 30.9 x 395mm M: 170mm - 140mm travel / 30.9 x 470mm L: 200mm - 170mm travel / 30.9 x 530mm XL: 200mm - 170mm travel / 30.9 x 530mm
SATTEL	Giant Romero
PEDALE	N/A
ANTRIEB	
SCHALTHABEL	SRAM SX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM SX Eagle
BREMSEN	Shimano BR-MT420, hydraulic, Shimano RT-26 rotors [F]180mm, [R]180mm
BREMSEBEL	Shimano BL-MT401
KASSETTE	SRAM SX Eagle, 11x50
KETTE	SRAM SX Eagle
KURBEL	SRAM SX Eagle PowerSpline, 30t S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	SRAM PowerSpline, threaded

LAUFRÄDER	
FELGEN	Giant AM 29 alloy, tubeless ready
NABE	[F] Giant Tracker Performance Boost 15x110, sealed bearing [R] Giant Tracker Giant Sport QR141, loose ball
SPEICHEN	Sapim
REIFEN	[F] Maxxis Minion DHF 29x2.5 WT, EXO, TR [R] Maxxis Dissector 29x2.4 WT, Dual, EXO, TR, tubeless
EXTRAS	tubeless prepared, max tire size 2.4", max chainring size 32t

## GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	400	425	450	475
SeatpostInsertionDepth (mm)	217	242	268	293
Sitzrohrwinkel	76.5°	76.5°	76.5°	76.5°
Oberrohrlänge (mm)	563	595	622	654
Steuerrohr-Länge (mm)	100	110	120	125
Steuerrohr-Winkel	65.5°	65.5°	65.5°	65.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	124.4	124.4	124.4	124.4
Radstand (mm)	1164	1198	1227	1260
Kettenstreben-Länge (mm)	440	440	440	440
Tretlager-Höhe (mm)	40	40	40	40
Stack (mm)	614	623	632	636
Reach (mm)	415	445	470	500
Überstandshöhe (mm)	735	734	753	758
Lenkerbreite (mm)	780	780	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	[F] 29" [R] 29"	[F] 29" [R] 29"	[F] 29" [R] 29"	[F] 29" [R] 29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.