



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Moonstone
RAHMEN	Advanced-grade composite front and rear triangles, 100mm FlexPoint Pro suspension, 12x148mm thru-axle
GABEL	Fox 34 Float SC Performance Remote, 110mm, GRIP damper, Boost 15x110 Kabolt, 44mm offset, remote lockout
DÄMPFER	Fox Float SL Performance Elite, three-position remote, 165/45, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact XC Flat, 760x35mm
GRIFFE	Giant XC Pro S:32mm, M:32mm, L:34mm, XL:34mm
VORBAU	Giant Contact SL XC, 35mm S:60mm, M:70mm, L:70mm, XL:70mm
SATTELSTÜTZE	Giant Contact Switch AT dropper 110-140mm travel / 30.9 x 395mm
SATTEL	Giant Grit SL
PEDALE	platform [GC,GT]
ANTRIEB	
SCHALTHEBEL	Shimano Deore XT SL-M8100, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano Deore XT RD-M8100
BREMSEN	Shimano SLX BR-M7100, hydraulic, Shimano RT-56 rotors [F]180mm, [R]160mm
BREMSHEBEL	Shimano Deore BL-M7100
KASSETTE	Shimano Deore XT M8100, 10x51
KETTE	KMC X-12
KURBEL	Shimano Deore XT 8120, 32t, 55mm chainline S:170mm, M:175mm, L:175mm, XL:175mm
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant XCR 2 29 Carbon WheelSystem
NABE	[F] Giant MTB alloy, 6-bolt, [R] Giant MTB alloy, 3-pawl driver, 6-bolt
SPEICHEN	Sapim
REIFEN	Maxxis Aspen 29x2.4, foldable, 120tpi, TLR, EXO, tubeless
EXTRAS	tubeless prepared, 2.4" max tire size, 34t max chainring size, Giant/MRP CS chain guide

GEOMETRIEDATEN

RAHMEN	S	M	L	XL
Sitzrohrlänge (mm)	390	420	465	495
Seat Post Insertion Depth (mm)	185	225	260	290
Sitzrohrwinkel	75.5°	75.5°	75.5°	75.5°
Oberrohrlänge (mm)	572	604	626	653
Steuerrohr-Länge (mm)	90	95	105	115
Steuerrohr-Winkel	67.5°	67.5°	67.5°	67.5°
Gabelneigung (mm)	44	44	44	44
Trail (mm)	109	109	109	109
Radstand (mm)	1127	1159	1183	1212
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	42	42	42	42
Stack (mm)	589	593	603	612
Reach (mm)	420	450	470	495
Überstandshöhe (mm)	745	750	777	800
Lenkerbreite (mm)	760	760	760	760
Vorbaulänge (mm)	60	70	70	70
Kurbellänge (mm)	170	175	175	175
Radgrösse	29"	29"	29"	29"

Spezifikations-, Preis- und Farbänderungen vorbehalten.