

DEFY ADVANCED PRO 0

GIANT



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Interstellar
RAHMEN	Advanced-Grade Composite, 12x142mm thru-axle, disc
GABEL	Advanced SL-Grade Composite, full-composite OverDrive Aero steerer, 12x100mm thru-axle, disc
DÄMPFER	N/A
KOMPONENTEN	
LENKER	Giant Contact SLR D-Fuse XS:40/42cm, S:40/42cm, M:42/44cm, M/L:42/44cm, L:44/46cm, XL:44/46cm
GRIFFE	Stratus Lite 3.0
VORBAU	Giant Contact SL AeroLight XS:80mm, S:90mm, M:100mm, M/L:100mm, L:110mm, XL:110mm
SATTELSTÜTZE	Giant D-Fuse SLR, composite, -5/+15mm offset
SATTEL	Giant Fleet SL
ANTRIEB	
SCHALTHABEL	Shimano Ultegra Di2 ST-R8170
UMWERFER	Shimano Ultegra Di2 FD-R8150
SCHALTWERK	Shimano Ultegra Di2 RD-R8150
BREMSEN	Shimano Ultegra Di2 hydraulic, Shimano RT-CL800 rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano Ultegra Di2
KASSETTE	Shimano Ultegra, 12-speed, 11x34
KETTE	Shimano Ultegra
KURBEL	Shimano Ultegra, 34/50 with Giant Power Pro power meter XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175
TRETLAGER	Shimano, press fit

LAUFRÄDER	
FELGEN	Giant SLR 1 36 Carbon Disc WheelSystem
NABE	[F] Giant Low Friction Hub, CenterLock, 12mm thru-axle, [R] Giant Low Friction Hub, 30t ratchet driver, CenterLock, 12mm thru-axle
SPEICHEN	Sapim
REIFEN	CADEX Classics, tubeless, 700x32c (33.5mm), folding
EXTRAS	computer mount, fender mount, water bottle cages, tubeless prepared, 38mm max tire size

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
Sitzrohrlänge (mm)	410	445	480	515	535	565
Sitzrohrwinkel	74.5°	74.0°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	515	530	545	560	575	595
Steuerrohr-Länge (mm)	120	140	150	175	195	215
Steuerrohr-Winkel	70.5°	71.8°	72.5°	72.5°	72.5°	72.5°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	71.6	63.4	58.6	58.6	58.6	58.6
Radstand (mm)	995	994	998	1010	1025	1040
Kettenstreben-Länge (mm)	420	420	420	420	420	420
Tretlager-Höhe (mm)	75	75	75	70	70	70
Stack (mm)	527	541	558	577	596	615
Reach (mm)	369	375	380	384	393	402
Überstandshöhe (mm)	705	733	762	796	814	841
Lenkerbreite (mm)	400	400	420	420	440	440
Vorbaulänge (mm)	80	90	100	100	110	110
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700C	700C	700C	700C	700C	700C

Spezifikations-, Preis- und Farbänderungen vorbehalten.