



## SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Black/Moonstone, Mars Dust
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMponenten	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	cork tape with gel
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, alloy, 14mm offset
SATTEL	Giant Approach
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-610, 2x12
UMWERFER	Shimano GRX RX-820
SCHALTWERK	Shimano GRX RX-820
BREMSEN	Shimano GRX RX-410 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-610 hydraulic
KASSETTE	Shimano 105, 11x34
KETTE	KMC X12L-1
KURBEL	FSA Omega Modular AGX+, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	FSA Mega EXO

LAUFRÄDER	
FELGEN	Giant S-X2 Disc wheelset, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	stainless
REIFEN	Giant Crosscut Grip TR, 700x40c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

## GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
	SHORT   LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600
Steuerrohr-Länge (mm)	125	135	150	165	180	195
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78   82	72   75	68   72	65   68	65   68	65
Radstand (mm)	1029   1039	1025   1035	1030   1040	1035   1045	1045   1055	1060
Kettenstreben-Länge (mm)	430   440	430   440	430   440	430   440	430   440	430
Tretlager-Höhe (mm)	80   81	80   81	80   81	80   81	80   81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Überstandshöhe (mm)	717   724	734   741	752   759	769   776	786   793	801
Lenkerbreite (mm)	420	420	440	440	460	460
Vorbaulänge (mm)	50	60	70	80	80	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C

Spezifikations-, Preis- und Farbänderungen vorbehalten.