



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, M/L, L, XL
FARBE	Metal/Shoreline, Pale Olive
RAHMEN	ALUXX-grade aluminum, 12x142mm thru-axle, disc, flip chip dropout
GABEL	Advanced-grade composite, full-composite OverDrive steerer, 12mm thru-axle, disc
KOMponenten	
LENKER	Giant Contact XR D-Fuse, 31.8mm XS:42cm, S:42cm, M:44cm, M/L:44cm, L:46cm, XL:46cm
GRIFFE	cork tape with gel
VORBAU	Giant Contact, 8-degree XS:50mm, S:60mm, M:70mm, M/L:80mm, L:80mm, XL:90mm
SATTELSTÜTZE	Giant D-Fuse, alloy, 14mm offset
SATTEL	Giant Approach
ANTRIEB	
SCHALTHEBEL	Shimano GRX RX-400, 2x10
UMWERFER	Shimano Tiagra
SCHALTWERK	Shimano GRX RX-400
BREMSEN	Shimano GRX RX-400 hydraulic, Giant MPH rotors [F]160mm, [R]160mm
BREMSHEBEL	Shimano GRX RX-400 hydraulic
KASSETTE	Shimano HG500, 11x34
KETTE	KMC X10 with Missing Link
KURBEL	FSA Omega Adventure, 32/48 XS:170mm, S:170mm, M:172.5mm, M/L:172.5mm, L:175mm, XL:175mm
TRETLAGER	FSA Mega EXO

LAUFRÄDER	
FELGEN	Giant S-X2 Disc wheelset, alloy
NABE	Giant alloy, 12mm thru-axle
SPEICHEN	stainless
REIFEN	Giant CrossCut AT 2, 700x38c, tubeless
EXTRAS	tubeless prepared, 53mm max tire size in "long" flip chip position, 45mm max tire size in "short" flip chip position

GEOMETRIEDATEN

RAHMEN	XS	S	M	ML	L	XL
	SHORT LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SHORT	LONG SH
Sitzrohrlänge (mm)	430	450	470	490	510	530
Sitzrohrwinkel	74.0°	73.5°	73.5°	73.0°	73.0°	73.0°
Oberrohrlänge (mm)	540	550	560	575	585	600
Steuerrohr-Länge (mm)	125	135	150	165	180	195
Steuerrohr-Winkel	70.0°	71.0°	71.5°	72.0°	72.0°	72.0°
Gabelneigung (mm)	50	50	50	50	50	50
Trail (mm)	78 82	72 75	68 72	65 68	65 68	65
Radstand (mm)	1029 1039	1025 1035	1030 1040	1035 1045	1045 1055	1060
Kettenstreben-Länge (mm)	430 440	430 440	430 440	430 440	430 440	430
Tretlager-Höhe (mm)	80 81	80 81	80 81	80 81	80 81	80
Stack (mm)	556	570	586	602	616	630
Reach (mm)	381	381	387	391	397	407
Überstandshöhe (mm)	717 724	734 741	752 759	769 776	786 793	801
Lenkerbreite (mm)	420	420	440	440	460	460
Vorbaulänge (mm)	50	60	70	80	80	90
Kurbellänge (mm)	170	170	172.5	172.5	175	175
Radgrösse	700x 42C	700x 42C	700x 42C	700x 42C	700x 42C	700

Spezifikations-, Preis- und Farbänderungen vorbehalten.