

TRANCE X ADVANCED 2



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	S, M, L, XL
FARBE	Sangria/Chrome
RAHMEN	Advanced-Grade Composite front and rear triangles, 140mm Maestro suspension, 12x148mm thru-axle, 27.5 or 29-inch rear wheel compatible, flip chip - Maestro 3, flip chip - headset, integrated down tube storage and under-top tube storage mounts
GABEL	Fox 36 Float Rhythm, 150mm, GRIP damper, 15x110 Kabolt X, 44mm offset
DÄMPFER	Fox Float Performance, 185/52.5, custom tuned for Giant
KOMPONENTEN	
LENKER	Giant Contact TR35, alloy, 780x35mm, 20mm rise
GRIFFE	Giant Tactal Pro Single Lock-On, 132x35mm
VORBAU	Giant Contact SL 35 S:40mm, M:40mm, L:50mm, XL:50mm
SATTELSTÜTZE	Contact Switch AT dropper, remote S: 110-140mm travel / 30.9 x 395mm M: 140-170mm travel / 30.9 x 470mm L: 170-200mm travel / 30.9 x 530mm XL: 170-200mm travel / 30.9 x 530mm
SATTEL	Giant Romero SL
PEDALE	N/A
ANTRIEB	
SCHALTHABEL	Shimano SLX M-7100, I-Spec EV, 1x12
UMWERFER	N/A
SCHALTWERK	Shimano SLX M-7100
BREMSEN	Shimano Deore BR-M6120, hydraulic, four piston, Shimano RT-66 rotors [F]203mm, [R]180mm
BREMSHEBEL	Shimano Deore BL-M6100
KASSETTE	Shimano SLX M7100, 10x51
KETTE	KMC X-12
KURBEL	Shimano MT512-1, 30t, 55mm chainline S:165mm, M:170mm, L:170mm, XL:170mm
TRETLAGER	Shimano Press Fit

LAUFRÄDER

FELGEN	Giant TRX WheelSystem, carbon, hookless, 30mm inner width, 40mm outer width, 22mm height, Wide Guard Technology
NABE	[F] Giant Alloy, 6 Bolt [R] TRX HE, Alloy, 72 Pawl Driver, 6 bolt
SPEICHEN	Sapim, 28, straight pull, DBL Technology
REIFEN	[F] Maxxis Minion DHF, 29x2.5 WT, 3C 60 tpi, MaxxTerra, EXO, TR [R] Maxxis Dissector 29x2.4 WT, 60 tpi, 3C MaxxTerra, TR, tubeless
EXTRAS	tubeless prepared, 2.5" max tire size, 34t max chainring size, 3M tailgate protector, down tube and chainstay protection

GEOMETRIEDATEN

RAHMEN	S			M			L			XL		
	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH	LOW	MID	HIGH
Sitzrohrlänge (mm)	400			425			450			475		
Seat Post Insertion Depth (mm)	280			305			330			355		
Sitzrohrwinkel	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°	76.8°	77.2°	77.5°
Oberrohrlänge (mm)	571	570	569	602	601	600	624	623	622	657	656	655
Steuerrohr-Länge (mm)	100			105			115			125		
Steuerrohr-Winkel	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°	64.4°	64.8°	65.1°
Gabelneigung (mm)	44			44			44			44		
Trail (mm)	134.1	131.3	128.4	134	131.3	128.5	133.9	131.3	128.5	133.9	131.3	128.5
Radstand (mm)	1190	1190	1189	1222	1222	1221	1246	1246	1245	1281	1280	1279
Kettenstreben-Länge (mm)	440	439	438	440	439	438	440	439	438	440	439	438
Tretlager-Höhe (mm)	40	35	30	40	35	30	40	35	30	40	35	30
Stack (mm)	617	614	611	621	619	616	631	628	625	640	637	634
Reach (mm)	426	430	434	456	460	464	476	480	484	507	510	514
Überstandshöhe (mm)	733	737	742	737	741	746	754	759	763	752	757	761
Lenkerbreite (mm)	800			800			800			800		
Vorbaulänge (mm)	40			40			50			50		
Kurbellänge (mm)	165			170			170			170		
Radgrösse	[F] 29" [R]			[F] 29" [R]			[F] 29" [R]			[F] 29" [R]		

Spezifikations-, Preis- und Farbänderungen vorbehalten.