



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	L
FARBE	Teal
RAHMEN	ALUXX SL-Grade Aluminum, 160mm Maestro Suspension
GABEL	RockShox Yari RC Solo Air, 160mm Travel, Boost 15x110 Maxle Lite, Tapered, Custom 46mm Offset
DÄMPFER	RockShox Deluxe RT, Trunnion Mount
KOMPONENTEN	
LENKER	Giant Contact SL DH,31.8mm
VORBAU	TruVativ Descendant
SATTELSTÜTZE	Giant Contact Switch Dropper post, 30.9mm
SATTEL	Liv Contact, (Upright)
ANTRIEB	
SCHALTHEBEL	Shimano SLX, 1x11
SCHALTWERK	Shimano SLX
BREMSEN	Shimano SLX [F]200mm[R] 180mm
BREMSHEBEL	Shimano SLX
KASSETTE	Shimano SLX, 11x46
KETTE	KMC X11-1
KURBEL	SRAM Descendent/6000 series Alloy, 30t with MRP AMG V2
LAUFRÄDER	
TRETLAGER	SRAM GXP PressFit
FELGEN	Giant P-AM2
NABE	[F] Giant Tracker Boost 15x110, Sealed Bearing [R] Giant Tracker 12x148, Sealed Bearing
SPEICHEN	Sapim
REIFEN	Maxxis Shorty 27.5x2.5 , 60 TPI, EXO, Tubeless [F], Maxxis High Roller II 27.5x2.4, 60 TPI, EXO, Tubeless [R]
EXTRAS	Factory Tubeless

MODELL-MERKMALE

- ALUXX SL-grade Aluminium frame with 160mm Maestro suspension
- RockShox Yari RC Solo Air 160mm fork
- RockShox Deluxe R trunnion mount shock
- Shimano SLX 1x11 speed drivetrain with MRP AMG v2 guide
- Giant Contact SL DH dropper seatpost
- Shimano SLX hydraulic disc brakes
- Color: Teal



GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	365	380	431	482
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	570	585	610	625
Steuerrohr-Länge (mm)	95	100	115	130
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	109	109	109	109
Radstand (mm)	1145	1160	1188	1205
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	5	5	5	5
Stack (mm)	576	580	594	608
Reach (mm)	404	418	439	450
Überstandshöhe (mm)	710	717	755	795
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	50	50	50	60
Kurbellänge (mm)	170	170	170	170
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.