



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Metallic Red / Black / Chrome
RAHMEN	ALUXX SL-Grade Aluminum front/rear triangles
GABEL	RockShox Lyric RC DebonAir, 170mm travel, Boost 15x110mm Maxle Stealth, tapered steerer, 46mm offset
DÄMPFER	RockShox Super Deluxe air RT twistLoc remote, trunnion mount
KOMPONENTEN	
LENKER	Giant Contact SL TR35, 35mm, 20mm rise
VORBAU	Giant Contact SL 35, 35mm
SATTELSTÜTZE	Giant Contact Switch S dropper post with remote lever, 30.9mm
SATTEL	Liv Contact (forward)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM GX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM GX Eagle
BREMSEN	SRAM Code R [F] 200mm [R] 180mm
BREMSHEBEL	SRAM Code R
KASSETTE	SRAM GX Eagle, 10x50
KETTE	SRAM GX
KURBEL	SRAM Descendent 6K Eagle Dub, 30
LAUFRÄDER	
TRETLAGER	SRAM GXP Dub Press Fit
FELGEN	Giant TR1, 30mm inner width, 27.5 hookless alloy WheelSystem
NABE	Level 2 hubs (F) Boost 15x110mm, (R) Boost 12x148, XD Driver body
SPEICHEN	Sapim
REIFEN	[F] Maxxis Minion DHF 27.5x2.5 WT, 60 TPI, EXO, TR [R] Maxxis DHR II 27.5x2.4 WT, 60 TPI, EXO, TR

MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum front/rear triangles
- Gabel: RockShox Lyric RC DebonAir, 170mm travel, Boost 15x110mm Maxle Stealth, tapered steerer, 46mm offset
- Schalthebel: SRAM GX Eagle, 1x12
- Kurbel: SRAM Descendent 6K Eagle Dub, 30
- Farbe: Metallic Red / Black / Chrome

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	365	380	431	482
Sitzrohrwinkel	74.0°	74.0°	74.0°	74.0°
Oberrohrlänge (mm)	570	585	610	625
Steuerrohr-Länge (mm)	95	100	115	130
Steuerrohr-Winkel	66.0°	66.0°	66.0°	66.0°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	109	109	109	109
Radstand (mm)	1145	1160	1188	1205
Kettenstreben-Länge (mm)	435	435	435	435
Tretlager-Höhe (mm)	5	5	5	5
Stack (mm)	576	580	594	608
Reach (mm)	404	418	439	450
Überstandshöhe (mm)	710	717	755	795
Lenkerbreite (mm)	800	800	800	800
Vorbaulänge (mm)	50	50	50	60
Kurbellänge (mm)	170	170	170	170
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.