

INTRIGUE E+ 2 PRO



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Metallic Red/Black
RAHMEN	ALUXX SL-grade aluminum, Advanced forged composite upper rocker, 140mm Maestro suspension system
GABEL	SR Suntour Aion 35 Air LO-R 27.5+ 150mm travel, Lockout, Boost 110x15mm Quick-Loc thru-axle
DÄMPFER	Fox Float DPS Performance, EVOL Large Volume sleeve, 3-position lever, 185x52.5mm Trunnion mount, custom tuned
KOMPONENTEN	
LENKER	Giant Contact 35 Trail
VORBAU	Giant Contact SL 35
SATTELSTÜTZE	Giant Contact Switch, dropper, 30,9mm, under bar remote lever
SATTEL	Liv Contact, Upright
PEDALE	-
ANTRIEB	
SCHALTHEBEL	Shimano Deore
UMWERFER	MRP 1X CS custom
SCHALTWERK	Shimano SLX, 10-Speed, Shadow+
BREMSEN	Tektro HD-M745 Orion, 4-piston, hydraulic disc, 203mm
BREMSHEBEL	Tektro HD-M745 Orion
KASSETTE	Shimano HG50-10 11-36T, 10-Speed
KETTE	KMC e.10 Turbo, e-bike optimized
KURBEL	Praxis 36T Cold Forged 4130 premium steel Wave Praxis e-Cadet+ custom forged crankarm set
LAUFRÄDER	
TRETLAGER	N/A
FELGEN	Giant AM 27.5+, Tubeless ready, 35mm inner width, e-bike optimized
NABE	Giant eTracker Boost, Sealed cartridge bearing, 6-bolt, [F] 110x15 [R] 148x12mm Thru-axle, e-bike optimized
SPEICHEN	Sapim E-Lite [r] Race [f], e-bike optimized
REIFEN	Maxxis Minion DHF 27.5x2.6" Foldable, Tubeless, EXO, Dual compound [F] Maxxis Rekon 27.5x2.6" Foldable, Tubeless, EXO, Dual Compound [R]
EXTRAS	Giant EnergyPak 6A Smart charger (60% charge in 60minutes) Tubeless kit
HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
SENSORS	Giant PedalPlus 4-sensor technology
DISPLAY	Giant RideControl One, remote button
BATTERY	Giant EnergyPak 500, 36V 13.8Ah integrated Lithium-Ion

MODELL-MERKMALE

- Giant SyncDrive Pro, 360% tuneable support, powered by YAMAHA
- Giant EnergyPak500 lithium-ion battery
- SR Suntour Aion 35 LO-R 150mm suspension fork
- Shimano Deore / SLX 2x10sp speed drivetrain
- Powerfull 4-piston hydraulic disc brakes
- Color: Metallic Red/Black"

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	380	406	445	482
Sitzrohrwinkel	74.5°	74.5°	74.5°	74.5°
Oberrohrlänge (mm)	565	580	595	620
Steuerrohr-Länge (mm)	95	100	105	125
Steuerrohr-Winkel	66.5°	66.5°	66.5°	66.5°
Gabelneigung (mm)	46	46	46	46
Trail (mm)	109	109	109	109
Radstand (mm)	1169	1185	1201	1229
Kettenstreben-Länge (mm)	470	470	470	470
Tretlager-Höhe (mm)	15	15	15	15
Stack (mm)	579	584	588	607
Reach (mm)	404	418	431	451
Überstandshöhe (mm)	707	725	753	781
Lenkerbreite (mm)	760	760	780	780
Vorbaulänge (mm)	40	40	50	50
Kurbellänge (mm)	165	170	170	170
Radgrösse	27.5+	27.5+	27.5+	27.5+

Spezifikations-, Preis- und Farbaenderungen vorbehalten.