



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Charcoal / Fuchsia / Caribbean Green
RAHMEN	ALUXX SL-Grade Aluminum front/rear triangles
GABEL	Fox 34 Performance, 130mm travel, Fit4 Damper, Boost QR15x110mm, tapered steerer
DÄMPFER	Fox Float DPS Performance, trunnion mount
KOMPONENTEN	
LENKER	Giant Contact Trail
VORBAU	Giant Contact 40mm(XS)50mm(S-M)60mm(L)
SATTELSTÜTZE	Giant Contact Switch dropper post with remote lever, 30.9mm
SATTEL	Liv Contact (forward)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM NX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM NX Eagle
BREMSEN	SRAM Guide T [F] 180mm [R] 160mm, hydraulic Disc
BREMSHEBEL	SRAM Guide T
KASSETTE	SRAM NX Eagle, 11x50
KETTE	SRAM NX
KURBEL	TruVativ Descendent 6k Eagle Dub, 30
LAUFRÄDER	
TRETLAGER	SRAM GXP Dub Press Fit
FELGEN	Giant AM 27.5 tubeless ready sleeve-joint rim, 30mm inner width
NABE	[F] Giant Tracker Boost 15x110mm, sealed bearing [R] Giant Tracker Boost 12x148, sealed bearing
SPEICHEN	Sapim
REIFEN	Maxxis Highroller II 27.5x2.3 60tpi EXO, tubeless

MODELL-MERKMALE

- Rahmen: ALUXX SL-Grade Aluminum front/rear triangles
- Gabel: Fox 34 Performance, 130mm travel, Fit4 Damper, Boost QR15x110mm, tapered steerer
- Schalthebel: SRAM NX Eagle, 1x12
- Kurbel: TruVativ Descendent 6k Eagle Dub, 30
- Farbe: Charcoal / Fuchsia / Caribbean Green

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	345	390	440	490
Sitzrohrwinkel	73.0°	72.5°	72.5°	72.5°
Oberrohrlänge (mm)	552	572	592	602
Steuerrohr-Länge (mm)	95	100	110	120
Steuerrohr-Winkel	69.4°	69.4°	69.4°	69.4°
Gabelneigung (mm)	42	42	42	42
Trail (mm)	88	88	88	88
Radstand (mm)	1058	1073	1094	1104
Kettenstreben-Länge (mm)	430	430	430	430
Tretlager-Höhe (mm)	21	21	21	21
Stack (mm)	581	586	595	605
Reach (mm)	374	387	404	411
Überstandshöhe (mm)	661	692	725	761
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	40	50	50	60
Kurbellänge (mm)	170	170	170	175
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.