



SPEZIFIKATIONEN

RAHMEN	
GRÖSSEN	XS, S, M, L
FARBE	Teal / True Blue
RAHMEN	Advanced-Grade Composite front triangle, ALUXX SL-Grade Aluminum rear triangle
GABEL	Fox 34 Float Performance Elite, 130mm travel, FIT4 Damper, Boost, 15x110mm KaBolt, tapered steerer
DÄMPFER	Fox Float DPS Performance Elite, trunnion mount
KOMPONENTEN	
LENKER	Giant Contact SL Trail
VORBAU	Giant Contact SL
SATTELSTÜTZE	Giant Contact Switch S dropper post with remote lever, 30.9mm
SATTEL	Liv Contact SL (forward)
PEDALE	N/A
ANTRIEB	
SCHALTHEBEL	SRAM NX Eagle, 1x12
UMWERFER	N/A
SCHALTWERK	SRAM NX Eagle
BREMSEN	SRAM Guide RS [F] 180mm [R]180mm
BREMSHEBEL	SRAM Guide RS
KASSETTE	SRAM NX Eagle, 11x50
KETTE	SRAM NX Eagle
KURBEL	TruVativ Descendent 6k Eagle Dub, 30
LAUFRÄDER	
TRETLAGER	SRAM GXP Dub Press Fit
FELGEN	Giant TRX 1, 30mm inner width, 27.5 hookless carbon WheelSystem
NABE	[F] Boost 15x110mm [R] Boost 12x148, Non XD Driver Body
REIFEN	Maxxis Highroller II 27.5x2.3 60tpi EXO, tubeless

MODELL-MERKMALE

- Rahmen: Advanced-Grade Composite front triangle, ALUXX SL-Grade Aluminum rear triangle
- Gabel: Fox 34 Float Performance Elite, 130mm travel, FIT4 Damper, Boost, 15x110mm KaBolt, tapered steerer
- Schalthebel: SRAM NX Eagle, 1x12
- Kurbel: TruVativ Descendent 6k Eagle Dub, 30
- Farbe: Teal / True Blue

GEOMETRIEDATEN

RAHMEN	XS	S	M	L
Sitzrohrlänge (mm)	345	390	440	490
Sitzrohrwinkel	73.0°	72.5°	72.5°	72.5°
Oberrohrlänge (mm)	552	572	592	602
Steuerrohr-Länge (mm)	95	100	110	120
Steuerrohr-Winkel	69.4°	69.4°	69.4°	69.4°
Gabelneigung (mm)	42	42	42	42
Trail (mm)	88	88	88	88
Radstand (mm)	1058	1073	1094	1104
Kettenstreben-Länge (mm)	430	430	430	430
Tretlager-Höhe (mm)	21	21	21	21
Stack (mm)	581	586	595	605
Reach (mm)	374	387	404	411
Überstandshöhe (mm)	661	692	719	755
Lenkerbreite (mm)	750	750	780	780
Vorbaulänge (mm)	40	50	50	60
Kurbellänge (mm)	170	170	170	175
Radgrösse	27.5"	27.5"	27.5"	27.5"

Spezifikations-, Preis- und Farbaenderungen vorbehalten.